

	ACCESS CONTROLLER PR622-G ROGER	ACCESS CONTROLLER MODULE MC16-PAC-EX-3 ROGER	IP CAMERA APTI-AI508C2IW-36AD Active Deterrence - 5 Mpx 3.6 mm
			
	128.74 EUR 128.74 EUR	694.71 EUR 694.71 EUR	79.67 EUR 79.67 EUR
Number of served transitions	...	3	...
Cards support	Unique EM 125kHz
Standard	IP
Inputs	...	18	...
Reading distance of prox-keys	max. 15 cm
Outputs	...	12	...
Autonomous operation	✓
Doorbell button	—
Number of users	...	max. 12000 - Number of identifiers	...
Relay contacts load	1.5 A / 30 V
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Number of permissions per ID	...	100	...
Keyboard built-in	—
Buffer memory	...	8 000 000 events buffer	...
Input lines	3
MCT readers support	...	16 pcs	...
Output lines	3
Tamper output	✓
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p
Readers connections	...	4 pcs - Wiegand / PRT	...
Number of login points	...	6	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Number of access terminals	...	12	...
Lens	3.6 mm
Number of access zones	...	6	...
View angle	80 °
Average current consumption	50 mA

Number of alarm zones	...	6	...
Range of IR illumination	25 m
Number of automation nodes	...	6	...
White light LED illuminator range	25 m
Memory card slot	Micro SD memory cards up to 1TB support (possible local recording)
Battery backup support	—	12 V / 7 Ah	...
Communication	<ul style="list-style-type: none"> • RS-485 • RACS (Roger) 	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Environment class	IV
Alarm inputs / outputs	1 / 1
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support, • Audio transmission via network
Main stream frame rate	max. 25 fps @ 5 Mpx
Main features	<ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PRT series readers support • 4000 indexed users • History of 32000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	...
Interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	10
ONVIF	19.12

Operation temp	-25 °C ... 60 °C	5 °C ... 40 °C	...
Intelligent image analysis	<ul style="list-style-type: none"> • intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles • detection of people gathering • loitering detection • motion detection based on human detection
Permissible relative humidity	10 ... 95 % (non-condensing)	10 % ... 95 % (non-condensing)	...
Main features	<ul style="list-style-type: none"> • Active intrusion deterrence works by blinking blue and red light and siren sound or voice prompts • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Smart motion detection (with recognizing people and vehicles) • Privacy zones - max. 3 • Image rotation and mirror • Day/Night mode - configurable • Sharpness - sharper image outlines
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	192.168.1.168
Default admin user / password	admin / admin
Web browser access ports	80
PC client access ports	80
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream

Power supply	10 ... 15 V DC	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 400 mA
Power consumption	≤ 4.8 W
Housing	Compact, Metal
Color	White
"Index of Protection"	IP67	...	IP67
Mechanical protection class	—
Operation temp	-30 °C ... 60 °C
Weight	0.15 kg	0.14 kg	0.55 kg
Dimensions	85 x 85 x 27 mm	175 x 72 x 30 mm	Ø 73 x 175 mm
Supported languages	Polish, English, French, Russian, Spanish, Portuguese, Italian, Ukrainian, Hungarian
Manufacturer / Brand	ROGER	ROGER	APTI
Guarantee	3 years	3 years	2 years

