




	HUB USB 3.0 F7U-U3-CR-BP 1 m	KEYSTONE CONNECTOR FX-C3	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER
			
	58.56 PLN 58.56 PLN	7.80 PLN 7.80 PLN	1400.00 PLN 1400.00 PLN
Number of served transitions	1
Inputs	8
Outputs	8
Connector type	...	Adapter CINCH Socket / CINCH Socket	...
Number of users	max. 12000 - Number of identifiers
Connectors	<ul style="list-style-type: none"> • 1 x Socket - micro USB 3.0 • 7 x socket - USB-A • 1 x Power socket - micro USB
Color	...	Yellow	...
Length of the cable	1 m
Application	...	Patch panel Keystone	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
USB standard	3.0
Impedance	...	75 Ω	...
Number of permissions per ID	100
Buffer memory	8 000 000 events buffer
Material	...	Metal / PET	...
MCT readers support	16 pcs
Readers connections	4 pcs - Wiegand / PRT
Number of login points	2
Number of access terminals	4
Number of access zones	2
Number of alarm zones	2
Number of automation nodes	2
Battery backup support	12 V / 7 Ah
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)

Main features	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the micro USB socket • LED indication • Transparent housing 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance • Keystone assembly standard 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	5 V DC / 3 A (power adapter not included)	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
Weight	0.050 kg	0.008 kg	0.14 kg
Dimensions	135 x 35 x 19 mm	16 x 21 x 30 mm (W x H x D)	175 x 72 x 30 mm
Manufacturer / Brand	ORICO	...	ROGER
Guarantee	2 years	2 years	3 years