



	EXTENDER VGA TRVGA-300-P	AHD, HD-CVI, HD-TVI CAMERA APTI-H50C4-2812G 2Mpx / 5Mpx 2.8 ... 12 mm
		
	122.12 EUR 122.12 EUR	49.56 EUR 49.56 EUR
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Device type	Active / Transmitter Active / Receiver	...
Number of channels	1 VGA 1 VGA	...
Video transmission range	max. 300 m max. 300 m	...
Symmetrical socket impedance	100 Ω 100 Ω	...
Range of IR illumination	...	40 m
Connectors type	VGA Socket VGA Socket female	...
IR illuminator power adjustment	...	Automatic
Symmetrical socket type	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket	...
Lens	...	2.8 ... 12 mm
Main features	<ul style="list-style-type: none"> • Short-circuit protection • Signal correction 	...
View angle	...	<ul style="list-style-type: none"> • 89 ° ... 27 ° (manufacturer data) • 80 ° ... 34 ° (our tests result)
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch

Resolution	<ul style="list-style-type: none"> • 1920 x 1200 / 80 Hz @ 100 m • 1024 x 768 / 60 Hz @ 300 m 	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	...	✓
Power supply	12 V / 70 mA (power adapter not included) 12 V / 170 mA (power adapter not included)	12 V DC / 410 mA
Power consumption	...	≤ 4.9 W
Housing	...	Compact - Metal
Color	...	Graphite
"Index of Protection"	...	IP67
Operation temp	...	-20 °C ... 60 °C
Weight	0.078 kg 0.078 kg	0.67 kg
Dimensions	118 x 30 x 48 mm 118 x 30 x 54 mm	210 x 88 x 84 mm
Supported languages	...	English
Manufacturer / Brand	DELTA	APTI
Guarantee	3 years	2 years