

	EXTENDER HDMI-EX-6IR	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-36 2Mpx / 5Mpx 3.6 mm	TV OR MONITOR MOUNT ADUX150 ART	ROUTER RG-EW300PRO 2.4 GHz 300 Mbps REYEE	POE SWITCH / EXTENDER PFT1320 3-PORT
					
	80.03 CAD 80.03 CAD	42.87 CAD 42.87 CAD	34.01 CAD 34.01 CAD	25.46 CAD 25.46 CAD	26.87 CAD 26.87 CAD
Frequency range	...	...	...	2.4 GHz	...
Standard	...	AHD, HD-CVI, HD-TVI	...	...	...
Antenna type	...	...	...	4 x Omnidirectional antenna - Integrated, 5 dBi @ 2.4 GHz 2x2 MU-MIMO	...
Sensor	...	1/3 " Progressive Scan CMOS	...	...	...
Mounting standard	...	...	VESA 200 x 200, 300 x 200, 300 x 300, 400 x 300, 400 x 400	...	...
Standards	...	...	...	IEEE 802.11 a/b/g/n	...
Matrix size	...	5 Mpx	...	...	...
Baud rates	...	...	...	300 Mbps	...
Supported HDMI resolutions	1080i - 50/60 Hz, 720p, 576p, 576i, 480p, 480i	...	...	...	...
Screen size range	...	...	23 " ... 60 "	...	...
Bearing capacity	...	...	45 kg	...	...
Distance from mounting surface	...	...	65 ... 350 mm	...	...
LAN ports	...	...	...	3 x 10/100 Mbps LAN 1 x 10/100 Mbps Uplink	• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
LED indicators	...	...	...	Status	...
Management	...	...	...	...	—
DDNS	...	...	...	✓	...
Maximal transmission range	• 45 m @ 720p / 1080i - UTP cat. 5 • 60 m @ 720p / 1080i - UTP cat. 6	...	...	...	...
Tilt adjustment	...	...	0 ° ... 15 °	...	...
DHCP server	...	...	...	✓	...
LED diodes	...	...	...	...	Link, Act
Firmware update	...	...	...	✓	...
Transmission speed	...	...	...	...	10 / 100 Mbps
Horizontal rotation	...	...	-45 ° ... 45 °	...	...
Rotation in the plane of the screen	...	...	—	...	...
Maximal output power	...	...	...	...	15.4 W @ port PoE - First device
Management interface	...	...	...	Web browser, Configuration using the Reyee Router application	...
Supported audio formats	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD	...	...	...	...
Mobile phones support	...	...	...	Android: Free application Reyee Router iOS (iPhone): Free application Reyee Router	...
Transmitter power	...	...	...	max. 20 dBm	...

Range	...	...	...	...	100 m - Input 100 m - Output
Protections	...	...	...	WPA/WPA2 TCP Flood network attacks protection	—
Operation temp. / Relative humidity	...	...	...	...	-30 ... 65 °C / 10 ... 90 %
Resolution	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps	...	...	...
Range of IR illumination	...	20 m	...	...	...
IR illuminator power adjustment	...	Automatic	...	...	...
Lens	...	3.6 mm	...	...	...
Main features	IR receiver : 20 ... 60 kHz	...	• A blockade to prevent the TV/monitor from slipping • Double arm guaranteeing stability and safety • Built-in bubble level for easy installation • In the kit : Expansion plugs, Screws	• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Static / dynamic routing • Built-in 3-port switch • Access Point • Remote management • DMZ • UPnP • Port forwarding • parental control • Guest Network - a separate and secure network for guests • DHCP client list • SSID hiding	• Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender
Operation temp	-10 °C ... 55 °C	...	...	0 °C ... 45 °C	...
View angle	...	• 77 ° (manufacturer data) • 70 ° (our tests result)	...	...	...
Permissible relative humidity	5 % ... 90 %	...	...	5 % ... 95 % (non-condensing)	...
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...	...	...
OSD menu	...	✓	...	...	...
Main features	...	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only	...	...	...
Housing	...	Dome - Metal	...	...	Plastic
Color	...	Graphite	Black	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Vandal-proof	...	—	...	...	...
"Index of Protection"	...	IP67	...	...	...
Power supply	5 V DC / 1000 mA - 2 pcs of power adapters included	12 V DC / 230 mA	...	12 V DC / 1 A (power adapter included)	PoE (802.3af/at)
Power consumption	...	≤ 2.8 W	...	≤ 12 W	0.3 W
Operation temp	...	-20 °C ... 60 °C	...	...	...
Weight	0.08 kg	0.42 kg	4.09 kg	0.26 kg	0.05 kg
Dimensions	72 x 67 x 25 mm	Ø 96 x 91 mm	435 x 420 x (65 ... 350) mm	210 x 180 x 33 mm	88 x 44 x 22 mm
Supported languages	...	Polish, English	...	...	...
Manufacturer / Brand	...	APTI	ART	RUIJIE / REYEE	...
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00