





	<a href="#">RFID PROXIMITY CARD ATLO-104N13</a>	<a href="#">PARKING SENSOR LED LIGHTING CONTROLLER PARKING-SENSOR/BLEBOX 7... 24 V DC</a>	<a href="#">DUAL SMART SWITCH SWITCHBOX-D-DIN/BLEBOX Wi-Fi, 230 V AC</a>	<a href="#">PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND</a>
				
	0.41 EUR 0.41 EUR	29.39 EUR 29.39 EUR	43.21 EUR 43.21 EUR	48.51 EUR 48.51 EUR
Standard	Unique EM 125kHz	...	...	...
Compatibility	EM4100/4102	...	...	...
Possibility of programming the serial number (ID)	—	...	...	...
Ability to write to internal memory	—	...	...	...
Application	...	<ul style="list-style-type: none"> <li>• It shows the distance between the moving object and the sensor by using LED lighting</li> <li>• Works with LED lighting - (RGB) 7-24V LED strips</li> </ul>	switching devices on/off	...
Maximal voltage	...	...	...	320 V AC, 50 / 60 Hz
Serial Number overprint	✓	...	...	...
Rated voltage	...	7 ... 24 V DC	230 V AC	230 / 400 V AC, 50 / 60 Hz
Class	...	...	...	1+2 type ( Class B+C )
Maximal total load	...	56 ... 192 W	2 x 1150 W (resistance load) / 2 x 150 W (inductive or capacitive load)	...
Total maximal current	...	8 A	2 x 5 A	...
Number of inputs	...	0	2	...
Number of outputs	...	4	2	...
Protection level Up	...	...	...	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)
Connector type	...	screw terminals	screw terminals	...
Wireless	...	—	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Nominal discharge current	...	...	...	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)
Mobile phones support	...	—	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>	...
Maximum stroke current	...	...	...	50 kA @ 8/20 µs (T2)
Operation state indication	...	...	...	✓

Main features	<ul style="list-style-type: none"> <li>Serial Number Format : 10H13D + WEG24A</li> <li>Range : ~ 11 cm</li> <li>The TK-4100 chip</li> </ul>	<ul style="list-style-type: none"> <li>Ultrasonic sensor,</li> <li>Outputs : "Open Collector" (OC) type 250 mA,</li> <li>Distance range of the virtual wall from the sensor : 2 ... 250 cm,</li> <li>Operation modes (distances to virtual wall) : <ul style="list-style-type: none"> <li>Green : 140 cm (safe distance)</li> <li>Blue : 48 ± 4 cm (obstacle close)</li> <li>Red : 17 ± 3 cm (stop the vehicle)</li> <li>Red (blinking) : 4 ± 2 cm (stop the vehicle immediately)</li> </ul> </li> <li>Additional output for space occupancy signaling,</li> <li>Small dimensions</li> </ul>	<ul style="list-style-type: none"> <li>Two output modes: independent and push-pull</li> <li>Local control by physical button,</li> <li>schedule,</li> <li>sunrise and sunset mode,</li> <li>timer,</li> <li>remote access,</li> <li>voice control,</li> <li>The ability to set the default status of the device after a power failure,</li> <li>Energy consumption metering,</li> <li>Power measurement,</li> <li>Charts and measurement history</li> <li>µWiFi technology support</li> <li>Illuminated, color front panel with an additional control button</li> </ul>	Varistor
Housing	...	Self-extinguishing	Plastic (ABS), DIN, TS-35 rail mounting	Plastic
"Index of Protection"	...	IP20	IP20	...
Color	...	Black	White	...
Operation temp	...	-20 °C ... 50 °C	-20 °C ... 50 °C	...
Weight	0.006 kg	0.06 kg	0.06 kg	0.098 kg
Dimensions	86 x 54 x 1 mm	51 x 58 x 25 mm	90 x 17.5 x 65 mm	62 x 54 x 17 mm
Manufacturer / Brand	ATLO	BleBox	BleBox	LEGRAND
Guarantee	2 years	2 years	2 years	2 years