





	EXTENDER ETHERNET+PoE_ETH- ETH500-SET ATTE	MEMORY CARD SD-10/32- SAND UHS-I, SDHC 32 GB SANDISK	MEMORY CARD TF- L100-128GB microSD UHS-I, SDXC 128 GB DAHUA	MEMORY CARD NM- N100-64GB NM Card 64 GB DAHUA
				
	60.02 EUR 60.02 EUR	8.19 EUR 8.19 EUR	21.26 EUR 21.26 EUR	14.82 EUR 14.82 EUR
Type	...	SD (Secure Digital)	microSD	NM Card
Type	...	UHS-I, SDHC	UHS-I, SDXC	...
LAN ports	2 x RJ45 10/100 Base-T + Passive PoE
Capacity	...	32 GB	128 GB	64 GB
Read speed	...	120 MB/s	≤ 100 MB/s	≤ 93 MB/s
Write transfer rate	≤ 30 MB/s	≤ 82 MB/s
LED diodes	LAN, PoE, 10Mb
UTP transmission range	< 800 m (max)
Transmission speed	10 / 100 Mbps : 2 LAN & PoE ports
Class	...	10, U1	10, U3, V30, A1	...
SD Adapter	—	—
Maximal output power	< 250 m - 100 Mbps - 50 W < 500 m - 100 Mbps - 25 W < 800 m - 10 Mbps - 15 W
Maximal total power	50 W
Main features	<ul style="list-style-type: none"> • Can be powered from a switch (PoE 802.3at/af, Passive PoE) and via screw connectors • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender • The output PoE voltage is equal to the input voltage 	...	<ul style="list-style-type: none"> • High and low temperature resistant (-25 °C ... 85 °C) • Waterproof • Anti-magnetic • Anti X-ray 	<ul style="list-style-type: none"> • High and low temperature resistant (-25 °C ... 85 °C) • Waterproof • Anti-magnetic • Anti X-ray • eMMC5.1 protocol • TLC Module
Power supply	44 ... 58 V DC - Passive PoE 12 ... 58 V DC - screw connectors
Power consumption	1.35 W
Weight	0.05 kg
Dimensions	73 x 52 x 20 mm (single element)	32 x 24 x 2 mm	15 x 11 x 1 mm	12.3 x 8.8 x 0.7 mm
Manufacturer / Brand	ATTE	SANDISK	DAHUA	DAHUA
Guarantee	3 years	2 years	2 years	3 years