



	SINGLE SURFACE SOCKET OUTLET HERMES/0321-09/EPN 250 V AC 16 A IP44 Elektro- Plast	INDUSTRIAL POE/EPOE SWITCH LR2110-8ET-120- V2 8-PORT SFP DAHUA
		
	83.00 CZK 83.00 CZK	4280.62 CZK 4280.62 CZK
Rated voltage	250 V AC	...
Maximal current load	16 A	...
Grounding	✓	...
Cable terminals	screw terminals	...
Socket type	CEE 7/5, Surface-mounted	...
Protection shutter	—	...
Assembly	Mounting screws	...
"Index of Protection"	IP44	...
IK rating	—	...
Color	Black	...
LAN ports	...	<ul style="list-style-type: none"> • 1 x port SFP 1000 Base-X - Uplink, • 1 x RJ45 10/100/1000 Base-T - Uplink, • 6 x RJ45 10/100 Base-T + ePoE / PoE (802.3af/at) - Color green, • 2 x RJ45 10/100 Base-T + PoE (802.3bt) / ePoE / PoE (802.3af/at) - Color : Red
Management	...	—
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps - 6 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 1 Port LAN - Uplink, • 1000 Mbps - 1 SFP ports - Uplink
Maximal output power	...	<ul style="list-style-type: none"> • 30 W / port PoE @ PoE (802.3af/at) or ePoE, • 90 W @ PoE (802.3bt)
Maximal total power	...	120 W
MAC addresses table	...	8k

Main features	<ul style="list-style-type: none"> • Hermes product series • Splash-proof casing • opening lid • For indoor use • For outdoor use • PN-EN 60884-1:2006 compliance 	<ul style="list-style-type: none"> • Auto-learning and Auto-aging functions support for MAC addresses • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Possibility to mount on a wall, or on the DIN TS-35 rail
LED diodes	...	Power, Link/Act
Power supply	...	54 V DC / 2.22 A (power adapter included)
Housing type	...	DIN
Operation temp	...	-30 °C ... 65 °C
Weight	0.094 kg	0.63 kg
Dimensions	65 x 75 x 48 mm	150 x 100 x 42 mm
Manufacturer / Brand	Elektro-Plast Nasielsk	DAHUA
Guarantee	5 years	5 years