




	<a href="#">IP SPEED DOME CAMERA OUTDOOR TC-H326S SPEC:33X/I/E+/A/V3.0 - 1080p 4.6 ... 152 mm TIANDY</a>	<a href="#">SWITCHING ADAPTER 12V/3A/GPV</a>	<a href="#">ROUTER RG-EG105G-P-V2, 4 PoE REYEE</a>
			
	1977.83 AUD 1977.83 AUD	18.43 AUD 18.43 AUD	264.43 AUD 264.43 AUD
Standard	IP	...	...
Adapter type	...	Switching	...
Sensor	1/2.8 " Progressive Scan CMOS	...	...
Power voltage	...	100 ... 240 V AC	...
Matrix size	2 Mpx	...	...
Frequency range	...	50 / 60 Hz	...
Output voltage	...	12 V DC	...
Standards	...	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at
Maximal load	...	3 A	...
Output power	...	36 W	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 720p	...	...
Number of outputs	...	1 pcs	...
Lens	4.6 ... 152 mm	...	...
LAN ports	...	...	• 3 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN & PoE / WAN 10/100/1000 Mbps (RJ-45)
Housing type	...	Plastic	...
WAN interface	...	...	• 1 x WAN x 10/100/1000 Mbps (RJ-45)
LED indicators	...	...	Status, Link/Act
View angle	• 60 ° ... 2.3 ° (manufacturer data) • 57 ° ... 2.8 ° (our tests result)	...	...
DDNS	...	...	✓
Optical zoom	x 33	...	...
DHCP server	...	...	✓
Port USB	...	...	—
Digital zoom	x 16	...	...
Firmware update	...	...	✓
Range of IR illumination	200 m	...	...

Video output	—	...	...
Preset rotation speed	<ul style="list-style-type: none"> <li>• 240 °/s (horizontal)</li> <li>• 120 °/s (vertical)</li> </ul>	...	...
Power supply PoE	...	...	Power output - LAN ports : PoE (802.3af/at) max. 54 W (total)
Rotation speed (manual control)	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 180 °/s (horizontal)</li> <li>• 0.1 °/s ... 120 °/s (vertical)</li> </ul>	...	...
Protections	...	<ul style="list-style-type: none"> <li>• Overload</li> <li>• Short-circuit</li> <li>• Overvoltage</li> </ul>	<ul style="list-style-type: none"> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> </ul>
Horizontal rotation range	360 ° - continuous	...	...
Vertical rotation range	-16 ° ... 90 °	...	...
Management interface	...	...	<ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>
RS-485 interface	✓	...	...
Number of presets	500	...	...
Horizontal scan	✓	...	...
Route settings	8	...	...
Image compression method	S+265 / H.265 / H.264 / MJPEG	...	...
Alarm inputs / outputs	1 / 1	...	...
Audio	<ul style="list-style-type: none"> <li>• Audio input</li> <li>• Audio output</li> </ul>	...	...
Main stream frame rate	25 fps @ 1080p	...	...
Network interface	10/100 Base-T (RJ-45)	...	...
WEB Server	Built-in	...	...

Main features	...	Box casing designed to wall mounting	<ul style="list-style-type: none"> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>
ONVIF	✓	...	...
Memory card slot	Micro SD card support up to 512GB	...	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>	...	Android: Free application <a href="#">Ruijie Reye</a> iOS (iPhone): Free application <a href="#">Ruijie Reye</a>
Operation temp	...	-20 °C ... 70 °C	0 °C ... 40 °C
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...	...
Permissible relative humidity	...	...	10 % ... 90 % (non-condensing)
Max. number of on-line users	≤ 7	...	...
Default IP address	192.168.1.2	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...	...
Mobile client access ports	3000, 3001	...	...
PC client access ports	3000, 3001	...	...
Port ONVIF	80	...	...

Intelligent image analysis	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• intrusion</li> <li>• abandoned/missing object</li> <li>• illegal parking</li> <li>• people counting</li> <li>• detection of people gathering</li> <li>• heat map</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• protective helmet detection</li> <li>• detection of persons on duty</li> <li>• face detection</li> <li>• Intelligent Object Tracking</li> <li>• video tampering</li> </ul>	...	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> </ul>	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC</li> </ul>	...	54 V DC / 1.15 A (power adapter included)
Power consumption	max. 24 W	...	max. 60 W (at full load)
Housing	Speed Dome, Aluminum	...	...



Color	White + Black	...	...
Operation temp	-30 °C ... 65 °C	...	...
"Index of Protection"	IP66	IP67	...
Vandal-proof	—	...	...
Weight	5.3 kg	0.21 kg	0.43 kg
Dimensions	Ø 226 x 372 mm (without bracket)	148 x 32 x 28 mm	207 x 109 x 28 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, Turkish, Russian, French, Dutch, Hebrew, German, Portuguese, Thai, Ukrainian, Vietnamese, Italian	...	...
Manufacturer / Brand	TIANDY	...	RUIJIE / REYEE
Guarantee	3 years	2 years	2 years