




	<a href="#">MULTI-FUNCTIONAL USB TESTER SP-UT01</a> Spacetronek	<a href="#">CABLES TESTER ST-248</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-T1A21-0280B</a> - 1080p 2.8 mm DAHUA
			
	24.21 EUR 24.21 EUR	6.73 EUR 6.73 EUR	46.39 EUR 46.39 EUR
Device type	Power meter via USB, USB-C, micro USB ports	...	...
Input socket type	1 x USB-A plug 1 x USB-C plug 1 x microSD socket	...	...
Tested cables	...	RJ45, UTP, FTP, BNC	...
Standard	...	...	AHD / HD-CVI / HD-TVI / PAL
Sensor	...	...	1/2.7 " Progressive Scan CMOS
Output socket type	1 x USB-A socket 1 x USB-C socket	...	...
Matrix size	...	...	2.1 Mpx
LCD display	0.96 "	...	...
DC voltage measurement	3.6 ... 32 V @ 0.01 V	...	...
Resolution	...	...	1920 x 1080 - 1080p 1280 x 720 - 720p
Range of IR illumination	...	...	20 m
IR illuminator power adjustment	...	...	Automatic
DC current measurement	0 ... 5.1 A @ 0.01 A	...	...
Lens	...	...	2.8 mm, F1.2
Power measurement	0 ... 150 W @ 0.01 W	...	...
View angle	...	...	• 103 ° (manufacturer data) • 100 ° (our tests result)
Battery capacity measurement	0 ... 99999 mAh @ 1 mAh	...	...
S/N ratio	...	...	> 65 dB
Impedance measurement	1 ... 999.9 Ω @ 0.1 Ω	...	...
Temperature measurement	0 ... 80 °C @ 1 °C	...	...
Video output	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Time display range	max. 999 h 59 min 59 s @ 1 s	...	...
Maximal load	150 W	...	...

Range of displayed cumulative electricity	0.000 ... 999999 mWh @ 1 mWh	...	...
Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	...	OSD menu available via recorder
"Index of Protection"	...	...	IP40
Power consumption	...	...	≤ 2.3
Standards	PD2.0, PD3.0, QC2.0, QC3.0, BC1.2 and others	...	...
Housing	Plastic	...	Dome, Plastic
Vandal-proof	...	...	—
Power supply	3.6 V DC - Port USB	9 V DC / 25 mA battery	12 V DC / 230 mA
Color	...	...	White
Operation temp	...	...	-40 °C ... 60 °C
Weight	0.17 kg	0.115 kg	0.08 kg
Dimensions	67 x 61 x 11 mm	103 x 97 x 27 mm	Ø 85 x 69 mm
Manufacturer / Brand	Spacetronik	...	DAHUA
Guarantee	2 years	2 years	3 years

