

	CONNECTION BOX PUH-3P-M20	NVR DS-7732NXI-I4/16P/S(E) 32 CHANNELS, 16 PoE ACUSENSE Hikvision
		
	2.89 EUR 2.89 EUR	1593.55 EUR 1593.55 EUR
Number of intakes	2	...
Standard	...	TCP/IP
Supported resolutions	...	max. 32 Mpx
Number of terminals	2 x 3 pcs	...
"Index of Protection"	IP68	...
Voltage insulation	450 V	...
Video outputs	...	2 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS There is a possibility to configure a SPOT function on one of the output
Cable diameter	Ø 5 ... Ø 10.5 mm	...
Wire gauge	0.5 ... 4 mm ²	...
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	max. 256 Mbps
Supported hard drives	...	4 x 10 TB SATA + 1 x eSATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Smart Search function Smart Playback function Records playback from max. 32 channels in the same time @ 1080p 1/4/6/8/9/16/25/36 channel synchronous playback
Network interface	...	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application
Network protocols	...	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
ONVIF	...	✓
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start

Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application Hik-Connect iOS: Free application Hik-Connect
Web browser access ports	...	80, 8000
PC client access ports	...	8000
Mobile client access ports	...	8000
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
USB	...	2 pcs USB 2.0 1 pcs USB 3.0
Serial ports	...	2 pcs RS-485 1 pcs RS-232
Alarm inputs / outputs	...	16 / 9
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others
Motion Detection	...	2.0
Intelligent image analysis	...	✓
Main features	...	<ul style="list-style-type: none"> • NVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Face recognition, Motion detection with human/vehicle silhouette recognition, Deep Learning technology • Filtering of false alarms based on the recognition of persons and vehicles • Comparison of faces with images from the database • supports 4 types of facial attributes extraction • Support for up to 16 face databases, including 50 000 face images • Smart search for a person based on a face photo • Cooperation with POS (Point of Sale) terminals • Power outputs : 12 V DC / 1 A, 12 V DC / 0.5 A (controlling) <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	16-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)
Maximum total switch load	...	200 W



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	...	100 ... 240 V AC / 50 ... 60 Hz
Power consumption	...	max. 30 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	...	4.57 kg
Dimensions	72 ... 80 x 24 x 24 mm	440 x 402 x 75 mm, RACK 19", 1.5U
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	303618606
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00