




	SMART DUAL VALVE FOR THE IRRIGATION SYSTEM ATLO-VR2G-BLE-TUYA Bluetooth BLE, Tuya Smart	POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-5-11-F 5-PORT ATTE	POWER SUPPLY ADAPTER 12V/1.5A/PROTEC
			
	20457.14 HUF 20457.14 HUF	70381.90 HUF 70381.90 HUF	1800.95 HUF 1800.95 HUF
Adapter type	Switching
Application	irrigation control - 2 Zones
Power voltage	230 V AC
Type (size)	3/4 "
Output voltage	12 V DC
Maximal load	1.5 A
Output power	18 W
Average active efficiency	85.3 %
Working pressure	0.05 ... 0.8 MPa / 7.25 ... 116 psi
Power consumption at no-load	< 0.1 W
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink, • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...
Protections	<ul style="list-style-type: none"> • Overload • Short-circuit
Number of outputs	1 pcs
Management	...	—	...
Opening/closing time	5 ... 10 s
Power connectors type	2.1/5.5 mm - Straight plug
Housing type	Plastic
LED diodes	...	AC, DC, CHARGING (battery charging), PoE	...
Wireless	<ul style="list-style-type: none"> • Bluetooth, • 2.4 GHz Wi-Fi IEEE 802.11 b/g/n - Bluetooth/Wi-Fi gateway
Radio communication range (at open area)	<ul style="list-style-type: none"> • 15 m - Bluetooth • The range limited only by the availability of the Wi-Fi network - Bluetooth/Wi-Fi gateway

Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 1 x Port Uplink, • 10 / 100 Mbps : 5 x Port LAN & PoE 	...
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Maximal output power	...	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN1 ... LAN4 ports, • 60 W @ Passive PoE - Port LAN5, • 30 W @ PoE (802.3af/at) - LAN1 ... LAN5 ports 	...
Maximal total power	...	60 W	...
Operation modes	...	<ul style="list-style-type: none"> • Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN6 ports • Long Range : 280 m @ 10 Mb/s - LAN1 ... LAN4 ports ; 100 m @ 10/100 Mb/s - LAN5, LAN6 ports 	...
Housing	Plastic (ABS) + Nylon, UV-resistant, Waterproof
"Index of Protection"	IP55	...	IP53
Color	Gray + Black
Operation temp	4.5 °C ... 45 °C	...	-30 °C ... 40 °C

Main features	<ul style="list-style-type: none"> • schedule, • timer, • manual watering (app or button), • delay after rain : 1 ... 7 days - the device will not turn on the sprinklers if it is raining, • remote access - Bluetooth/Wi-Fi gateway (included), • voice control • 2 x STATUS indicator • Low current consumption • Easy installation - the valve is mounted directly on the tap • 2 x 3/4" / 1/2" Adapter (included) 	<ul style="list-style-type: none"> • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • Place for battery : 12 V / 18 Ah • Battery charging current : 1 A / 2 A - (set with the JP1 jumper) • Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery • Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF) • PSU thermal protection : 130 °C • Overload protection • LAN & PoE ports - Short-circuit protection, Overvoltage • TAMPER switch indicating open the cover • "Index of Protection" : IP20 	Splash-proof casing
Power supply	4 x 1.5V, type AA/LR6/FR6 battery (not included)	190 ... 260 V AC	...
Weight	0.4 kg	2.4 kg	0.17 kg
Dimensions	141 x 122 x 58 mm	325 x 305 x 100 mm	130 x 80 x 38 mm
Manufacturer / Brand	...	ATTE	...
Guarantee	2 years	3 years	2 years