



	NVR APTI-N6428AI-I3 64 CHANNELS	CABLE SCYY-6X0.5
		
	403.42 EUR 403.42 EUR	0.20 EUR 0.20 EUR
Standard	TCP/IP	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
In section	...	100 m . Price for 1m when buying a whole roll
Video outputs	<ul style="list-style-type: none"> • 1 pcs HDMI 4K • 1 pcs HDMI • 1 pcs VGA 	...
Inner conductor	...	6 x Ø 0.5 mm Al/Cu Stranded wire
Outer coating	...	PVC
Coating color	...	White
Audio support	<ul style="list-style-type: none"> • 64 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard 	...
Audio inputs	1 pcs CINCH	...
Application	...	<ul style="list-style-type: none"> • Alarm installation • Interphone installation
Audio outputs	1 pcs CINCH	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Bitrate	640 Mbps	...
Supported hard drives	8 x 10 TB SATA + 1 x eSATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...

Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...
Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	...
ONVIF	✓	...
Default IP address	192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	80, 5000, 554	...
PC client access ports	80, 5000, 554	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • Android: Free application BitVision, iOS: Free application iVMS320 	...
USB	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 1 pcs USB 3.0 	...
Serial ports	RS-485	...
Alarm inputs / outputs	16 / 4	...
PTZ control	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 control 	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
Intelligent image analysis	✓	...
Main features	<ul style="list-style-type: none"> • Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	...
Power consumption	≤ 20 W (without HDD)	...
Operation temp	-10 °C ... 50 °C	...
Weight	7.46 kg	...
Dimensions	440 x 430 x 100 mm	...

Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00