



	SWITCH POE CS4006-4GT-60 4-PORT DAHUA	AHD, HD-CVI, HD-TVI CAMERA APTI- H50C61-2812W 2Mpx / 5Mpx 2.8 ... 12 mm
		
	140.24 EUR 140.24 EUR	55.71 EUR 55.71 EUR
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports 	...
Maximal total power	60 W	...
MAC addresses table	8k	...
Management	✓	...
Resolution	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI
Range of IR illumination	...	60 m
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 ... 12 mm
LED diodes	Power, System, PoE, Link/Act	...
View angle	...	<ul style="list-style-type: none"> • 95 ° ... 30 ° (manufacturer data) • 87 ° ... 33 ° (our tests result)
S/N ratio	...	> 50 dB

Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - Via OSD, selectable by switch
Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall 	...
Certificates	CE	...
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	...	✓
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Housing	Desktop, Metal	Compact - Metal

Color	...	White
"Index of Protection"	...	IP66
Operation temp	...	-20 °C ... 60 °C
Power supply	53 V DC / 1.22 A (power adapter included)	12 V DC / 410 mA
Power consumption	max. 65 W	≤ 4.9 W
Operation temp	-10 °C ... 55 °C	...
Weight	0.3 kg	0.68 kg
Dimensions	130 x 90 x 26 mm	210 x 88 x 84 mm
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	DAHUA	APTI
Guarantee	3 years	2 years