





	PCB CLEANER PCB-CLEANER/1000 METAL CANISTER 1000 ml AG TERMOPASTY	EXTENDER HDMI+USB-EX-100	INDOOR PANEL IP VTH2421FW-P DAHUA	EXPANSION PLUG KS-12/8X60 KLIMAS
				
	124.18 SEK 124.18 SEK	1204.84 SEK 1204.84 SEK	3332.41 SEK 3332.41 SEK	3.39 SEK 3.39 SEK
Compatibility	Interphone installation - DAHUA	...
Package	Metal canister 1000 ml
Shield	7 " TFT-LCD color matrix	...
Resolution	1024 x 600	...
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Internal memory	8 GB	...
Drilling diameter	12 mm
Expansion plug length	60 mm
Supported HDMI resolutions	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Maximal transmission range	...	100 m UTP cat. 5e, 6
Screw dimensions	Ø 8 x 60 mm, SW-13
Max. number of receivers working in the same time	...	253
Protocols	...	HDBiT
Application	Ideal for removing dirt from optical components	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Main features	...	<ul style="list-style-type: none"> • The need for a separate power supply for the transmitter and receiver
Permissible relative humidity	...	0 % ... 90 % (non-condensing)

Main features	...	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network 	<ul style="list-style-type: none"> • Micro SD memory cards up to 32GB support (possible local recording), included : 8 GB, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • The ability to automatically take and save photos if you do not answer to the bell button, • The ability to record a short video message in the absence of a response to the bell button, • IP Dahua cameras support, • Built-in tenant list and list of connections, • Noise and echo reduction , 	...
Controlling	capacitive touch screen	...
Alarm inputs	6	...
Alarm outputs	1	...
Power supply	...	2 x 5 V DC / 1 A (power adapter included)	<ul style="list-style-type: none"> • 12 V DC / 500 mA, • 48 V PoE (802.3af) 	...
Power consumption	<ul style="list-style-type: none"> ≤ 6 W (operation) ≤ 4 W (Standby mode) 	...
Operation temp	...	-10 °C ... 60 °C	-10 °C ... 55 °C	...
Color	Black + White	...
Weight	0.857 kg	0.168 kg	0.35 kg	...
Dimensions	199 x 116 x 62 mm	110 x 89 x 26 mm - Transmitter or receiver dimensions	222 x 120 x 22 mm	...
Supported languages	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian	...
Manufacturer / Brand	AG TERMOPASTY	...	DAHUA	KLIMAS
Guarantee	...	2 years	3 years	2 years