


	POE POWER ADAPTER RG-POE-AT30 31.2 W REYEE	ACCESS CONTROLLER ASC2202B-D DAHUA
		
	41.29 CAD 41.29 CAD	394.72 CAD 394.72 CAD
Number of served transitions	...	2 (two-way)
Standards	Passive PoE	...
Support	...	DAHUA
Number of supported readers	...	4 pcs
Input voltage	100 V ... 240 V AC	...
Battery backup support	...	—
Output voltage	52 V DC	...
Maximal output current	0.6 A	...
Output lines	...	4 pcs - Relay
Number of inputs	1	...
Connector	2 x RJ-45 socket	...
Supported data rates	1 Gb/s	...
LED indicators	Power connection	...
Output power	31.2 W	...
Communication	...	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Housing	Plastic	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1.4 A
Pin numbers for RJ-45 connector	DATA : 1, 2 and 3, 6 Power supply : 4, 5 (+) and 7, 8 (-)	...
Certificates	CE	...

Main features	...	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Default IP address	...	192.168.0.2
Operation temp. / Relative humidity	-10 °C ... 45 °C / 5 % ... 95 % (non-condensing)	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Operation temp	...	-30 °C ... 60 °C
Permissible relative humidity	...	max. 95 % (non-condensing)
Weight	0.17 kg	0.4 kg
Dimensions	116 x 53 x 33 mm	210 x 106 x 50 mm
Manufacturer / Brand	RUIJIE / REYEE	DAHUA
Guarantee	3 years	3 years