







	ROUTER RG-EG105G-V2 REYEE	ROUTER RG-EG310GH-E REYEE	LED FLOODLIGHT WITH MOTION SENSOR AD-NL-6252BLR4 ADVITI	RFID PROXIMITY CARD ATLO-104N*P200	HEX HEAD SCREW SS-M8X20/KL-8.8	LAMINATED PVC CARD ATLO-100
						
	139.72 EUR 139.72 EUR	310.41 EUR 310.41 EUR	12.31 EUR 12.31 EUR	59.79 EUR 59.79 EUR	0.14 EUR 0.14 EUR	0.17 EUR 0.17 EUR
Luminous flux	800 lm
Size	M8	...
Material	Steel galvanized	...
Strength class	8.8	...
In package	200 pcs The price for package
Light color	Neutral, 4000 K
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z
Standard	Unique EM 125kHz	...	—
Twilight switch	✓
Wrench size	13 mm	...
Compatibility	EM4100/4102
Thread length	20 mm	...
Possibility of programming the serial number (ID)	—
Nominal power	10 W
Ability to write to internal memory	—
LAN ports	• 3 x LAN 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45)	• 6 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Serial Number overprint	✓
Power factor	0.8
WAN interface	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	• 1 x WAN x 10/100/1000 Mbps (RJ-45)
LED indicators	Status, Link/Act	Status, Link/Act
CRI	> 80
DDNS	✓	✓
DHCP server	✓	✓
Port USB	—	—
Firmware update	✓	✓
Power supply PoE	—	—
Protections	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks
Management interface	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser
Mobile phones support	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye
Housing	Aluminum
"Index of Protection"	IP44

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • View topology and network status • RESET button 	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip 	DIN 933 compliance	...
Power supply	12 V DC / 0.5 A (power adapter included)	100 ... 240 V AC, 50 / 60 Hz	230 V AC
Power consumption	max. 6 W	≤ 15 W
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C	-20 °C ... 50 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	0.4 kg	2.4 kg	0.22 kg	0.006 kg	0.012 kg	0.006 kg
Dimensions	207 x 109 x 28 mm	440 x 207 x 44 mm	105 x 130 x 65 mm	86 x 54 x 1 mm	...	86 x 54 x 1 mm
Manufacturer / Brand	RUIJIE / REYEE	RUIJIE / REYEE	ORNO / ADVITI	ATLO	...	ATLO
Guarantee	2 years	2 years	3 years	2 years	2 years	2 years