



	CONVERTER HDMI-OFT-20IR	SWITCH POE IP-5-11-E 5-PORT ATTE
		
	166.11 EUR 166.11 EUR	127.16 EUR 127.16 EUR
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Management	...	—
Outputs	1 pcs LC 1 pcs JACK IR transmitter 1 pcs HDMI	...
Inputs	1 pcs HDMI 1 pcs LC 1 pcs JACK IR receiver	...
LED diodes	...	Power, LAN
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Supported HDMI input resolutions	480i @ 60Hz 480p @ 60Hz 576i @ 50Hz 576p @ 50Hz 720p @ 50/60Hz 1080i @ 50/60Hz 1080p @ 50/60Hz	...
Supported HDMI output resolutions	480p @ 60Hz 576p @ 50Hz 720p @ 50/60Hz 1080p @ 50/60Hz	...
Optical wavelength	<ul style="list-style-type: none"> • 1310 nm • 1550 nm 	...
Connector type	LC	...
Fiber optic type	SMF 0-40km	...
Receiver sensitivity	≤ -32 dBm	...
Maximal output power	...	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports
Output power	≥ -11 dBm	...
Maximal total power	...	96 W
Attenuation	≤ 14 dB	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

IR frequency	38 kHz	...
Operation modes	...	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 • Port LAN 6 - Uplink
Main features	...	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules
Power supply	...	230 V AC - cable terminals
Weight	...	1.4 kg
Dimensions	138 x 79 x 25 mm	255 x 205 x 95 mm
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years