

	SEPARATOR WITH VIDEO BALUN D-SEP/HD-4/TR	MULTI-PURPOSE AGENT K2-07/150ML SPRAY 150 ml K2	SWITCHING ADAPTER 12V/41A/B	SWITCH POE DS-3E0518P-E 16-PORT SFP Hikvision
				
	24.38 EUR 24.38 EUR	2.54 EUR 2.54 EUR	20.74 EUR 20.74 EUR	296.37 EUR 296.37 EUR
Adapter type	Switching	...
Package	...	Spray 150 ml
Power voltage	110 / 230 V AC	...
Output voltage	12 V DC	...
Output voltage adjustment	10.3 ... 13.7 V	...
Maximal load	41 A	...
Output power	500 W	...
Number of fan coolers	1 pcs	...
Standard	<ul style="list-style-type: none"> • AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload 	...
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-TX (16 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-TX - Uplink, • 1 x port SFP 10/100/1000 Base-TX - Uplink
Application	...	<ul style="list-style-type: none"> • Elimination of squeaks, • Lubrication, • Removal of water, • Penetration, • Corrosion protection, • Surface preservation, • Removal of dirt
Operation temp. / Relative humidity	-10 °C ... 60 °C / 20 % ... 90 %	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power	30 W / port PoE
Maximal total power	230 W
Video transmission range	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL / NTSC - UTP cat. 5e
MAC addresses table	8k
Device type	Passive
Management	—

Number of channels	4 pcs Video
Number of inputs	4 pcs cable terminals
Number of outputs	4 pcs BNC socket	...	3 pcs	...
Input impedance	100 Ω
Output impedance	75 Ω
Opto-isolation between inputs and outputs	50 V DC
Main features	...	<ul style="list-style-type: none"> • Spray formulation with a straw for easy application in hard-to-reach places • Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places • It can be used in any position, even upside down 	...	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Overvoltage protection : 6 kV - PoE ports • Can be mounted in a Rack 19" cabinet
Galvanic separation between individual channels	> 2000 V
LED diodes	Power, Link/Act, PoE, PoE Max
Certificates	CE, FCC, RoHS
Housing	Metal
Attenuation	<ul style="list-style-type: none"> • 4.43 MHz @ 0.34 dB • 11 MHz @ 0.49 dB • 21 MHz @ 0.71 dB • 38 MHz @ 1.00 dB • 42 MHz @ 1.08 dB • 67.5 MHz @ 1.70 dB The attenuation applies to two devices connected to each other
Bandwidth	200 MHz
CMRR (dB @ 5MHz)	50 dB
SAP Code	301801378
Inputs protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A (t _p =8/20μs)
Power supply	—	100 ... 240 V AC
Operation temp	-20 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.09 kg	0.15 kg	1.38 kg	2.6 kg
Dimensions	103 x 75 x 30 mm	Ø 52 x 143 mm	241 x 124 x 66 mm	440 x 221 x 44 mm
Manufacturer / Brand	DELTA	K2	...	Hikvision
Guarantee	3 years	...	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00