




	<a href="#">SMART LIGHTING DIMMER DIMMERBOX-V2/BLEBOX Wi-Fi, 230 V AC</a>	<a href="#">ANGULAR SPEAKER PLUG WG2/KAT</a>	<a href="#">SWITCH POE IP-5-11-M2 5-PORT ATTE</a>
			
	31.23 GBP 31.23 GBP	0.20 GBP 0.20 GBP	97.01 GBP 97.01 GBP
Application	lighting brightness control	...	...
Rated voltage	230 V AC	...	...
Connector type	...	plug / screw terminals	...
Material	...	PET / Metal	...
Application	...	Speaker cable	...
Maximal total load	<ul style="list-style-type: none"> <li>• 250 W (resistance load),</li> <li>• 30 W (inductive or capacitive load - e.g. LED lamp)</li> </ul>	...	...
LAN ports	...	...	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Total maximal current	1.1 A	...	...
Number of inputs	2	...	...
Number of outputs	1	...	...
Management	...	...	—
Connector type	screw terminals	...	...
LED diodes	...	...	Power, LAN
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	...
Transmission speed	...	...	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>	...	...
Maximal output power	...	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>
Maximal total power	...	...	96 W
Housing	Plastic	...	...
"Index of Protection"	IP20	...	...

Color	Black	Black	...
Operation temp	-20 °C ... 50 °C	...	...
Operation modes	...	...	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure,</li> <li>• µWiFi technology support</li> </ul>	...	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement</li> </ul>
Power supply	...	...	230 V AC - cable terminals
Weight	0.04 kg	0.002 kg	0.65 kg
Dimensions	41 x 39 x 24 mm	18.5 x 11 x 11 mm	226 x 148 x 80 mm
Manufacturer / Brand	BleBox	...	ATTE
Guarantee	2 years	2 years	3 years