





	POWER SUPPLY ADAPTER 12V/4A/5.5	VIDEO AND POWER TRANSMITTERS VIA COAXIAL CABLE POC-P201	CABLE ATE-AVIA/AHD 0.32 m AUTONE	LED LIGHTING CONTROLLER FUT036S 2.4 GHz, MONO 12 ... 24 V DC MiBOXER / Mi-Light
				
	65.69 DKK 65.69 DKK	83.18 DKK 83.18 DKK	40.16 DKK 40.16 DKK	35.14 DKK 35.14 DKK
Device type	...	Active
Model identifier	12V/4A/5.5
Standard	...	CVBS - PAL / NTSC
Application	Works with LED lighting - single-color (MONO) 12-24V LED strips
Cable	BNC plug + 2.1/5.5 mm plug / M12, 4-pin socket - Code A	...
Number of channels	...	1 Video 1 DC
Length of the cable	0.32 m	...
Rated voltage	12 ... 24 V DC
AC input frequency	50 / 60 Hz
Application	ATE mobile recorders and cameras	...
Video transmission range	...	800 m RG59
Output current	4.0 A
Output power	48.0 W
Average efficiency during work	87.8 %
Efficiency at low load (10%)	84.5 %
Maximal total load	• 144 W @ 12 V, • 288 W @ 24 V
Input voltage	100 - 240 V AC	24 ... 36 V DC - (power adapter not included)
No-load power consumption	< 0.10 W
Total maximal current	12 A
Adapter type	Switching
Number of inputs	1
Output voltage	12.0 V DC	12 V max. 1 A DC
Protections	Overload
Output voltage adjustment	—
Number of outputs	1 pcs	2 (power)
Connector type	• screw terminals, • 5.5/2.1 socket / screw terminals - power input

Power connectors type	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug
Wireless	2.4 GHz
Housing type	Desktop
Radio communication range (at open area)	30 m
Mobile phones support	—
Main features	Very easy and quick assembly	The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control
Housing	Plastic
Color	White
Operation temp	-10 °C ... 40 °C
Manufacturer / Brand	AUTONE	MiBOXER / Mi-Light
Coaxial socket type	...	• Transmitter "A" BNC Straight socket Video BNC Plug with cable Video 2.1 / 5.5 mm Socket DC • Transmitter "B" BNC Straight socket Video BNC Plug with cable Video 2.1 / 5.5 mm Plug DC
Weight	0.31 kg	0.055 kg	0.028 kg	0.03 kg
Dimensions	120 x 55 x 38 mm	77 x 36 x 26 mm	...	75 x 36 x 17 mm
DC 12V power sending distance	...	• 300 m @ 500 mA - RG59 • 400 m @ 400 mA - RG59 • 600 m @ 280 mA - RG59 • 800 m @ 200 mA - RG59 • 400 m @ 500 mA - TRISET
Guarantee	2 years	2 years	2 years	2 years