



	<a href="#">IP SPEED DOME CAMERA OUTDOOR OMEGA-51P18-8P - 5 Mpx 5.35 ... 96.3 mm</a>	<a href="#">RFID PROXIMITY CARD ATLO-114*P10</a>
		
	251.39 EUR 251.39 EUR	5.05 EUR 5.05 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
In package	...	<b>10 pcs The price for package</b>
Standard	...	Unique EM 125kHz
Compatibility	...	EM4100/4102
Possibility of programming the serial number (ID)	...	—
Ability to write to internal memory	...	—
Serial Number overprint	...	—
Main features	...	<ul style="list-style-type: none"> <li>• Range : ~ 15 cm</li> <li>• The TK-4100 chip</li> </ul>
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	5.35 ... 96.3 mm	...
View angle	<ul style="list-style-type: none"> <li>• 59 ° ... 3.6 ° (manufacturer data)</li> <li>• 48 ° ... 3.7 ° (our tests result)</li> </ul>	...
Optical zoom	x 18	...
Auto IR illuminator	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	80 m	...
Video output	—	...
Rotation speed (manual control)	1 °/s ... 80 °/s (horizontal) 1 °/s ... 40 °/s (vertical)	...
Horizontal rotation range	360 ° continuous	...
Vertical rotation range	0 ° ... 93 °	...
RS-485 interface	—	...
Number of presets	255	...
Horizontal scan	✓	...
Image compression method	H.265 / H.264	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	Overvoltage	...
Alarm inputs / outputs	—	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 5 Mpx</li> <li>• 25 fps @ 4 Mpx</li> </ul>	...
WEB Server	Built-in	...
ONVIF	✓	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
Port ONVIF	8999	...
RTSP URL	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream	...
Route settings	8	...
OSD menu	preset 95	...



Main features	<ul style="list-style-type: none"> <li>• Intelligent image analysis : intrusion, motion detection based on human detection, video tampering</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Auto White Balance</li> <li>• IR illuminator optimization</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3 A (power adapter included)</li> </ul>	...
Power consumption	≤ 33 W	...
Housing	Speed Dome, Metal	...
Color	White + Black	...
"Index of Protection"	IP66	...
Operation temp	-20 °C ... 60 °C	...
Weight	1.5 kg (with bracket)	0.006 kg
Dimensions	200 x 269 x 137 mm (with bracket)	85 x 54 x 2 mm
Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	OMEGA	ATLO
Guarantee	2 years	2 years