



	ACCESS POINT RB-D52G-5HACD2HND-TC-HAP-AC2 hAP ac², 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps MIKROTIK	IP CAMERA F2C-PV Wi-Fi, Smart Dual Light Active Deterrence - 1080p 2.8 mm DAHUA
		
	87.75 EUR 87.75 EUR	40.42 EUR 40.42 EUR
Standard	...	IP
Frequency range	2.4 GHz, 5 GHz	...
Antenna type	4 x Internal antenna	...
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz	...
Baud rates	300 Mbps + 867 Mbps	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor	...	1/3 " Progressive Scan CMOS
Lens	...	2.8 mm
LAN ports	4 x 10 / 100 / 1000 Mbps LAN 1 x 10 / 100 / 1000 Mbps Uplink	...
View angle	...	98 °
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
Memory card slot	...	Micro SD card support up to 256GB
LED indicators	Power, User, 4 x Ethernet, WAN, WPS	...
Image compression method	...	H.265 / H.264 H.264B / H.264H
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support
Main stream frame rate	...	25 fps @ 1080p
Interface	...	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45)
WEB Server	...	Built-in
ONVIF	...	✓
Intelligent image analysis	...	Human detection
Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 1M : -100 dBm • 11M : -94 dBm • 6M : -96 dBm • 54M : -78 dBm • MCS0 : -96 • MCS7 : -73 5 GHz : <ul style="list-style-type: none"> • 6M : -96 dBm • 54M : -80 dBm • MCS0 : -96 dBm • MCS7 : -75 dBm • MCS9 : -70 dBm 	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

DDNS	✓	...
DHCP server	✓	...
Main features	...	<ul style="list-style-type: none"> • Active deterrence function • Smart Dual Light • Built-in hybrid illuminator (LED - IR/white) • Day/night mode • ICR - Movable InfraRed filter • D-WDR - Wide Dynamic Range • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection
Firmware update	✓	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Management interface	Web browser	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Transmitter power	max. 27 dBm @ 2.4 GHz max. 26 dBm @ 5 GHz	...
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haso@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haso@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply	<ul style="list-style-type: none"> • 12 ... 30 V DC / 0.8 A (power adapter included) • 18 ... 28 V DC - Passive PoE 	12 V DC / 1 A (power adapter included)
Power consumption	...	≤ 6.5 W @ 12 V DC
Main features	<ul style="list-style-type: none"> • Built-in 4-port switch • The WPS function allows to easy establish an encrypted connection • WMM (Wi-Fi Multimedia) • Port USB • IPsec • Mode button 	...
Housing	...	Compact - Plastic
Operation temp	-40 °C ... 50 °C	...
Color	...	White + Black
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	0.17 kg	0.26 kg
Dimensions	120 x 99 x 33 mm	131 x 78 x 97 mm
Supported languages	...	Polish, English

Manufacturer / Brand	MikroTik	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00