




	CEE-PLUG PCE-0246 400 V 32 A 4P 6H IP44 / IP54	AHD, HD-CVI, HD-TVI CAMERA APTI-H53V21-36W - 8.3 Mpx 4K UHD 3.6 mm	IP CAMERA DH-IPC-HUM8101 PINHOLE - 1.3 Mpx 3.6 mm DAHUA
			
	7.50 CAD 7.50 CAD	50.70 CAD 50.70 CAD	656.58 CAD 656.58 CAD
Rated voltage	400 V / 50 ... 60 Hz
Standard	...	AHD, HD-CVI, HD-TVI	TCP/IP
Maximal current load	32 A
Number of poles	4P
Sensor	...	1/2.5 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Grounding	6h
Matrix size	...	8.3 Mpx	1.3 Mpx
Electrical cable	max. 4 x 6 mm ²
Cable terminals	screw terminals
Plug type	CEE
Contact material	CuZn
Maximum wire insulation diameter	20 mm
Min. illumination	0.01 Lux / F2.8
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
RS-485 interface	—
Resolution	...	<ul style="list-style-type: none"> • 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI / HD-CVI @ 12.5 fps, 20 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 	1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p 704 x 576 - D1 , 352 x 288 - CIF
RS-232 interface	✓
Range of IR illumination	...	25 m	...
IR illuminator power adjustment	...	Automatic	...
Lens	...	3.6 mm	3.6 mm (pinhole)
Bitrate	48 ... 8192 kbps - H.264
Main stream frame rate	25 fps @ 1280 x 960
View angle	...	<ul style="list-style-type: none"> • 77 ° (manufacturer data) • 83 ° (our tests result) 	<ul style="list-style-type: none"> • 83 ° (manufacturer data) • 72 ° (our tests result)
S/N ratio	...	> 50 dB	> 50 dB
Network protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, FTP, NTP
ONVIF	2.42
Image compression method	H.264 / MJPEG
Network interface	10/100 Base-T (RJ-45)
Alarm inputs / outputs	2 / 2
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...

Mobile phones support	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	admin / admin
Default IP address	192.168.1.108
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
OSD menu	...	✓	...
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Housing	...	Dome - Metal	...
Color	Red	White	...
Memory card slot	Cards support max. 64 GB
"Index of Protection"	IP44 / IP54	IP67	...
Vandal-proof	...	—	...
Power supply	...	12 V DC / 260 mA	• 12 V DC / 580 mA, • PoE (802.3af)
Power consumption	...	≤ 3.1 W	< 7 W
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Configurable Privacy Zones • IVS analysis - crossing the line (tripwire), intrusion, abandoned/missing object, scene changing, face detection
Length of the cable	8 m
Operation temp	...	-20 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.2 kg	0.43 kg	0.20 kg - Network module 0.22 kg - Camera
Dimensions	150 x 80 x 67 mm	Ø 97 x 91 mm	110 x 83 x 24 mm - Network module Ø 27 x 49 mm - Camera
Supported languages	English, Polish
Manufacturer / Brand	PCE	APTI	DAHUA
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00