



	DOORPHONE PROGRAMMING INTERFACE PRO-USB/2.0 ACQ	ROUTER VPN TL-ER605 TP-LINK
		
	16120.00 HUF 16120.00 HUF	25920.95 HUF 25920.95 HUF
Compatibility	COMO-PRO, GLASS-PRO monitors	...
Standards	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q
LAN ports	...	• 2 x LAN 10/100/1000 Mbps (RJ-45) • 2 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Connectors	<ul style="list-style-type: none"> • 1 pcs mini USB - Computer interface • 2 pcs RJ45 Control panel BUS • 3 pcs ARK connectors : system communication line connection: "LINE", power connection: "+DC" and "-DC" 	...
Supported operating systems	Windows	...
WAN interface	...	<ul style="list-style-type: none"> • 2 x LAN/WAN 10/100/1000 Mbps (RJ-45) • 1 x WAN x 10/100/1000 Mbps (RJ-45) • 1 x USB WAN - 3G/4G
LED indicators	...	Power, System, WAN, LAN, USB
DDNS	...	<ul style="list-style-type: none"> • DynDNS • No-IP • Peanuthull • Comexe
DHCP server	...	✓
Port USB	...	USB 2.0
Firmware update	...	✓

Protections	...	<ul style="list-style-type: none"> • SPI network firewall • VPN Passthrough • FTP/H.323/PPTP/SIP/IPsec ALG • Support DoS defence • Support Ping of Death defence • URL addresses filtering • Support ARP defence • IP-MAC Binding • TCP/UDP/ICMP Flood network attacks protection • TCP (Stealth FIN/Xmas/Null) scan blocking • Ping packets blocking from WAN • Access control
Management interface	...	<ul style="list-style-type: none"> • Omada Central Management System • Software Omada Controller • Omada Hardware Controller • Remote management • Web browser
Main features	...	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN, VPN Pass-through • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • MAC address cloning • DHCP client/server support • IPv6 compliance • IEEE 802.1Q VLAN • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • DMZ • IEEE 802.1x and Radius Authentication • SNMPv1/v2c/v3(MIB-2) • Reboot schedule • View topology and network status • RESET button
Power supply	...	12 V DC / 1 A (power adapter included)
Power consumption	...	max. 7.94 W

Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.040 kg	0.374 kg
Dimensions	71 x 70 x 19.5 mm	158 x 101 x 25 mm
Manufacturer / Brand	ACO	TP-LINK
Guarantee	2 years	5 years