

	ACCESS CONTROLLER ASC2102B-T DAHUA	BUFFERED SWITCHING POWER SUPPLY ADAPTER PSBEN-2012B	DIRECTIONAL ANTENNA DIGIT-ACTIVA/DVB-T	INSULATION RESISTANCE METER + RCD TESTER UT-582+ UNI-T
				
	69711.54 HUF 69711.54 HUF	26923.08 HUF 26923.08 HUF	15500.96 HUF 15500.96 HUF	55023.08 HUF 55023.08 HUF
Adapter type	...	Transforming
Number of served transitions	2 (two-way)
Input voltage	...	230 V AC
Receiving channels	21 ... 69	...
Support	DAHUA ASC2204C-H
Gain	max. 4.5 dBi	...
Output voltage	...	11 V ... 13.8 V (buffer operation)
Number of supported readers	4 pcs
AC voltage measurement	30 V ... 600 V ± (3% + 3) @ 1 V
Polarization	Horizontal	...
Max. output current (total)	...	2 A (max)
Battery backup support	—
Impedance	75 Ω	...
Battery charging current	...	0.2 A / 0.6 switchable
Output lines	5 pcs - Relay
Frequency measurement	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes
Power	...	31 W
Alarm inputs / outputs	5 / 1
Number of outputs	...	1
Communication	<ul style="list-style-type: none"> • RS-485, • Wiegand 34/26, • Control panel CAN (Controler Area Network)
Main features	...	<ul style="list-style-type: none"> • LED display • Intelligent management of Power Supply Unit power's output stage • Microprocessor-based automation system • Free software "PowerSecurity" for monitoring the Power Supply Unit operation parameters • Output voltage control • Load current control

Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Overheat • Tamper • Reverse polarity connection • Discharge • Overcharge
Test of RCDs	<ul style="list-style-type: none"> • Working voltage: 220V ± 10 % • Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : <ul style="list-style-type: none"> - x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms - x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms - x 5 - 500 mA @ 300 ms - AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms • AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time)
Automatic change of measuring ranges	—
RS-232	—
USB	—
Adapter operation control	...	<ul style="list-style-type: none"> • AC input voltage presence indication AC • DC output voltage presence indication DC • EPS FLT output - indicating AC power collapse • APS FLT output - Battery fault indication • PSU FLT output - Power Supply Unit fault indication • Failure codes with history display
Place for battery	...	12V/7Ah
Supported norms	...	PN-EN50131-6, 1÷3
Max. battery dimensions	...	250 x 130 x 75 mm



Main features	<ul style="list-style-type: none"> • 20 000 indexed users • History of 30 000 events • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Door Left Open and Door Forced Open alarms • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail 	...	<ul style="list-style-type: none"> • Gain : 0 ... 18 dB • It has a tight and UV-resistant housing • Small dimensions • Power supply : 12 V / 45 mA (power adapter included) 	<ul style="list-style-type: none"> • Phase switch 0° / 180° during RCD test, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction
Operation temp	-30 °C ... 60 °C	0 °C ... 40 °C
Permissible relative humidity	max. 95 % (non-condensing)	≤ 80 % (non-condensing)
Operation temp. / Relative humidity	...	-10 ... 40 °C / 20 ... 90 %
Power supply	12 V DC / 1 A	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight	0.384 kg	3.4 kg	0.7 kg	0.380 kg
Dimensions	209 x 117 x 51 mm	270 x 250 x 88 mm	350 x 325 x 150 mm	160 x 100 x 69 mm
Manufacturer / Brand	DAHUA	PULSAR	TELMOR	UNI-T
Guarantee	3 years	2 years	2 years	2 years