



	<a href="#">EXTENDER HDMI+USB-EX-70-4KV2</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TH-I8-0360B-S2 5 Mpx 3.6 mm DAHUA</a>
		
	176.54 EUR 176.54 EUR	81.25 EUR 81.25 EUR
Supported HDMI resolutions	max. 4K UHD @ 60 Hz	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Maximal transmission range	<ul style="list-style-type: none"> <li>• 60 m - UTP cat. 6, 6A, 7 @ 4K UHD (manufacturer data)</li> <li>• 70 m - UTP cat. 5e @ 1080p (our tests result)</li> <li>• 20 m - UTP cat. 5e @ 4K UHD (our tests result)</li> <li>• 60 m - UTP cat. 6 @ 4K UHD (our tests result)</li> </ul>	...
Resolution	...	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD-CVI only 960 x 576 - 960H, PAL
Lens	...	3.6 mm
View angle	...	<ul style="list-style-type: none"> <li>• 92 ° (manufacturer data)</li> <li>• 88 ° (our tests result)</li> </ul>
Range of IR illumination	...	80 m
IR illuminator power adjustment	...	Automatic
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> <li>• Very good image quality with no visible distortions caused by compression,</li> <li>• No delays in video transmission,</li> <li>• No delays in mouse control operations</li> <li>• Designed to continuous operation 24/7</li> </ul>	...
Audio	...	—
OSD menu	...	OSD menu available via DAHUA recorder

Operation temp	-20 °C ... 60 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...
Main features	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> <li>• Support KVM function,</li> <li>• HDR10 support</li> <li>• Transition of the HDMI signal in the transmitter</li> <li>• EDID support</li> <li>• ESD protection</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Sharpness - sharper image outlines</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> </ul>
Power supply	5 V DC / 1 A - 2 pcs (included)	12 V DC / 440 mA
Power consumption	...	≤ 5.2 W
Housing	...	Compact, Plastic + Metal
Color	...	White + Black
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.12 kg	0.41 kg
Dimensions	85 x 75 x 20 mm - Transmitter or receiver dimensions	Ø 90 x 241 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years