



	IP SPEED DOME CAMERA OUTDOOR TC-H326S SPEC:33X/I/E+/A/V3.0 - 1080p 4.6 ... 152 mm TIANDY	AUDIO SPLITTER CDNAR/U-DIN ACO
		
	5084.00 PLN 5084.00 PLN	118.29 PLN 118.29 PLN
Standard	IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Compatibility	...	ACO CDNP, Inspiro, Familio
Matrix size	2 Mpx	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 720p	...
Inputs	...	4 x ARK connectors : • Audio • Power supply 1 x RJ45 : • connecting audio, differential VIDEO signals and power
Lens	4.6 ... 152 mm	...
View angle	• 60 ° ... 2.3 ° (manufacturer data) • 57 ° ... 2.8 ° (our tests result)	...
Outputs	...	4 x RJ45 : • audio signal and power outputs 1 x RJ45 : • differential VIDEO signal, audio signal and power output
Optical zoom	x 33	...
Digital zoom	x 16	...
Range of IR illumination	200 m	...
Main features	...	• Pass-through output, for audio and video signals • It can work as pass- through or final splitter of the main bus line • Connecting 5 receivers or splitting the main bus line
Video output	—	...

Protections	...	Outputs to the receiver are protected on the power line with a polymer fuse
Preset rotation speed	<ul style="list-style-type: none"> • 240 °/s (horizontal) • 120 °/s (vertical) 	...
Rotation speed (manual control)	<ul style="list-style-type: none"> • 0.1 °/s ... 180 °/s (horizontal) • 0.1 °/s ... 120 °/s (vertical) 	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-16 ° ... 90 °	...
RS-485 interface	✓	...
Number of presets	500	...
Horizontal scan	✓	...
Route settings	8	...
Image compression method	S+265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • Audio input • Audio output 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
ONVIF	✓	...
Memory card slot	Micro SD card support up to 512GB	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus 	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Max. number of on-line users	≤ 7	...
Default IP address	192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...

PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • double crossing the line • intrusion • abandoned/missing object • illegal parking • people counting • detection of people gathering • heat map • detection of loitering in a given area • running • protective helmet detection • detection of persons on duty • face detection • Intelligent Object Tracking • video tampering 	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Motion Detection • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions 	...



Power supply	• PoE (802.3at), • 12 V DC	...
Power consumption	max. 24 W	...
Housing	Speed Dome, Aluminum	...
Color	White + Black	...
Operation temp	-30 °C ... 65 °C	...
"Index of Protection"	IP66	...
Vandal-proof	—	...
Weight	5.3 kg	0.111 kg
Dimensions	Ø 226 x 372 mm (without bracket)	101 x 70 x 59 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, Turkish, Russian, French, Dutch, Hebrew, German, Portuguese, Thai, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	ACO
Guarantee	3 years	2 years