


	<a href="#">WIRELESS DOOR CHIME ATLO-DBB-TUYA</a>	<a href="#">ROUTER ER-X EdgeMAX UBIQUITI</a>
		
	5.89 EUR 5.89 EUR	66.93 EUR 66.93 EUR
Signaling mode	Optical - sound signaling	...
Standards	...	IEEE 802.3ad, IEEE 802.1q
Number of ring-tones	52	...
Processor	...	Dual-Core 880 MHz, MIPS1004Kc
LAN ports	...	5 x LAN 10/100/1000 Mbps (RJ-45)
Volume adjustment	4 volume levels, 10 ... 90 dB	...
WAN interface	...	configurable
Operation range	80 m in open area	...
LED indicators	...	Power, LAN
Frequency band	433.92 MHz $\pm$ 0.2	...
DDNS	...	✓
DHCP server	...	✓
Color	Black	...
Protections	...	<ul style="list-style-type: none"> <li>• NAT network firewall</li> <li>• LAN ACL</li> <li>• Contact/Air (ESD/EMP) : <math>\pm</math> 24 kV / <math>\pm</math> 24 kV</li> </ul>
Management interface	...	<ul style="list-style-type: none"> <li>• Software EdgeOS, Software PC</li> <li>• Remote management</li> <li>• Web browser</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• Low power consumption</li> <li>• Receiver sensitivity : -110 dBm</li> <li>• Simple and quick device installation</li> </ul>	<ul style="list-style-type: none"> <li>• IEEE 802.1Q VLAN</li> <li>• PPPoE</li> <li>• Static routing</li> <li>• DHCP</li> <li>• IPv6 compliance</li> <li>• IGMP</li> <li>• NAT</li> <li>• VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN</li> <li>• Dynamic DNS</li> <li>• Client - Radius support</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols</li> <li>• View topology and network status</li> <li>• RESET button</li> <li>• Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+" : 4, 5 pins; "-" : 7, 8 pins)</li> <li>• Possibility to mount to the wall</li> </ul>
Power supply PoE	...	Ubiquiti Passive PoE
Power supply	100 ... 240 V AC	<ul style="list-style-type: none"> <li>• 12 V DC / 0.5 A (power adapter included)</li> <li>• Passive PoE 24 V - port eth0/PoE IN</li> </ul>
Power consumption	≤ 0.5 W	max. 5 W
Housing	Plastic	Metal
Operation temp	...	-10 °C ... 45 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.06 kg	0.172 kg
Dimensions	82 x 82 x 65 mm	110 x 75 x 22 mm
Manufacturer / Brand	...	UBIQUITI
Guarantee	2 years	2 years