


	AHD_HD-CVI_HD-TVI PAL CAMERA HAC-HFW2249T-I8-A-NI-0360B Full-Color - 1080p 3.6 mm DAHUA	MECHANICAL SPLICE WITH SC/APC CONNECTOR FAST-SC-APC	TV OR MONITOR MOUNT MC-711N MACLEAN	MEASUREMENT CABLE RJ11-W/LSA-W/2/2M	CABLE 2C-W/2C-G-3.0M 3 m	EXTENSION CABLE DC-2.1/5.5-WG-10M 10 m
						
	174.10 EUR 174.10 EUR	0.82 EUR 0.82 EUR	14.45 EUR 14.45 EUR	1.53 EUR 1.53 EUR	1.09 EUR 1.09 EUR	5.98 EUR 5.98 EUR
Fiber type	...	Single-mode	...	...	...	...
Fiber diameter	...	125 µm	...	...	...	...
Standard	AHD, HD-CVI, HD-TVI, CVBS	...	...	...	...	...
Sensor	1/2.8" Progressive Scan CMOS	...	...	...	...	...
Cable	...	...	...	RJ11 : Plug / LSA : Plug	2 x CINCH Plug / 2 x CINCH Socket	...
Connector type	...	SC-APC	...	...	...	1 x Ø 2.1/5.5 mm Straight socket 1 x Ø 2.1/5.5 mm Straight plug
Matrix size	2.1 Mpx	...	...	...	...	...
Length of the cable	...	...	...	2 m	3 m	10 m
Cable diameter	...	3 mm / 2 mm / 900 µm / 250 µm	...	...	...	...
Main features	...	...	...	• Solid workmanship • Very flexible	• Very easy and quick assembly	...
Rated voltage	...	...	...	...	...	12 V DC
Mounting standard	...	...	VESA : 75, 100, 200x100, 200, 300x200, 300, 400x200, 400x300, 400	...	...	...
Splice reuse	...	max. 5 times	...	...	...	...
Screen size range	...	...	26" ... 55"	...	...	...
Bearing capacity	...	...	30 kg	...	...	...
Distance from mounting surface	...	...	63 ... 415 mm	...	...	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL	...	...	...	...	...
Range of IR illumination	—	...	...	...	...	...
IR illuminator power adjustment	—	...	...	...	...	...
Tilt adjustment	...	...	-15° ... 10°	...	...	...
IR illuminator support	—	...	...	...	...	...
Lens	3.6 mm	...	...	...	...	...
Horizontal rotation	...	...	-90° ... 90°	...	...	...
Rotation in the plane of the screen	...	...	± 3°	...	...	...
View angle	• 90° (manufacturer data) • 84° (our tests result)	...	...	...	...	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	...	...	...	...
Audio	• Microphone built-in - HD-CVI only, • External microphone input - HD-CVI only	...	...	...	...	...
Main features	• WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • D-ZOOM - Digital Zoom • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Sharpness - sharper image outlines	...	...	...	...	...
OSD menu	OSD menu available via DAHUA recorder	...	...	...	...	...
Power supply	12 V DC / 200 mA	...	...	...	...	...
Power consumption	≤ 2.4 W	...	...	...	...	...
Housing	Compact, Aluminum	...	...	...	...	...
Color	White	...	Black	...	...	Black

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Vandal-proof	—	...	...	...	...	...
"Index of Protection"	IP67	...	...	...	...	...
Operation temp	-40 °C ... 60 °C	...	...	...	...	...
Weight	0.77 kg	...	2.93 kg	0.03 kg	0.073 kg	0.245 kg
Dimensions	244 x 90 x 90 mm	...	455 x 420 x (63 ... 415) mm	...	...	...
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian	...	...	...	...	...
Manufacturer / Brand	DAHUA	...	MACLEAN	...	...	...
Guarantee	5 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00