




	<a href="#">SMART SWITCH WITH TEMPERATURE AND HUMIDITY MEASUREMENT ATLO-TSH2-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">QUAD SMART LED LIGHTING CONTROLLER ATLO-SW4-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">REMOTE CONTROL FOR LED LIGHTING CONTROLLERS FUT007 2.4 GHz, MONO, CCT MiBOXER / Mi-Light</a>
			
	23.30 EUR 23.30 EUR	19.85 EUR 19.85 EUR	4.94 EUR 4.94 EUR
Application	temperature and humidity measurement switching devices on/off	switching devices on/off	Works with LED lighting : single-color (MONO) 12-24V LED strips, white LED strips with adjustable color temperature (CCT) 12-24V
Number of channels	...	4	4
Temperature measurement	-40 °C ... 80 °C ± 0.5 °C	...	...
Radio communication range (at open area)	...	...	30 m
Measurement of humidity	0 % ... 99 % ± 3 %	...	...
Power supply	90 ... 250 V	100 ... 240 V AC, 50 / 60 Hz	2 x 1.5V, type AAA/LR03 battery (not included)
Maximal total load	3750 W	4 x 150W W	...
Total maximal current	15 A	4 x 2.5 A	...
Number of inputs	1	4	...
Number of outputs	2	4	...
Connector type	screw terminals	screw terminals	...
Radio communication range	...	< 100 m (open area)	...
Wireless	Wi-Fi 2.4 GHz IEEE 802.11 b/g/n Bluetooth	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth	2.4 GHz
Mobile phones support	The <a href="#">Tuya Smart</a> free application on Android The <a href="#">Tuya Smart</a> free application on iOS	• The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS	...
Manufacturer / Brand	...	...	MiBOXER / Mi-Light
"Index of Protection"	...	IP20	...

Main features	<ul style="list-style-type: none"> <li>• Warning indication about exceeding the preset temperature,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Pairing button,</li> <li>• Wi-Fi indicator,</li> <li>• Temperature history graph,</li> <li>• For indoor use</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure</li> </ul>	Large, readable buttons
Housing	Plastic	Plastic	Plastic
Color	White	White	White
Operation temp	0 °C ... 40 °C	-10 °C ... 40 °C	-20 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)	...	...
Weight	0.1 kg (total)	0.03 kg	0.04 kg (without battery)
Dimensions	<ul style="list-style-type: none"> <li>• 96 x 54 x 29 mm</li> <li>• 100 cm (cable length)</li> </ul> Probe	43 x 39 x 22 mm	110 x 53 x 21 mm
Guarantee	2 years	2 years	2 years