



	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision	SMART ACTION TRIGGER ACTIONBOX-S/BLEBOX Wi-Fi, 230 V AC
		
	13330.37 DKK 13330.37 DKK	163.87 DKK 163.87 DKK
Application	...	controlling devices, triggering actions
Rated voltage	...	230 V AC
Maximal total load	...	—
Scanning system	Progressive	...
Total maximal current	...	—
Number of inputs	...	1
Number of outputs	...	0
Resolution	1920 x 1080 - 1080p	...
Connector type	...	screw terminals
Sensor	CMOS Uncooled VOx microbolometer	...
Matrix size	2.1 Mpx 120 x 160 px	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Temperature measurement	✓	...
Mobile phones support	...	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Temperature measurement range	30 °C ... 45 °C	...
Accuracy of temperature measurement	± 0.5 °C	...
Temperature measurement distance	0.3 ... 1.8 m	...
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	~ 5 cm	...
Face recognition distance	0.3 m ... 1.8 m	...

Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • µWiFi technology support
Memory	Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events	...
Standard	TCP/IP	...
IR illuminator	✓	...
LED illuminator	✓	...
Video output	—	...
Operation temp	...	-20 °C ... 50 °C
RS-485 interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	2 / 1	...
Audio	Speaker built-in	...
Network interface	10/100/1000 Base-T (RJ-45)	...
Network protocols	TCP/IP	...
WEB Server	—	...
ONVIF	—	...
RS-485	✓	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
PC client access ports	port 8000	...

Main features	<ul style="list-style-type: none"> • Detection of people without a mask - access denied or voice alerts • Temperature measurement • 7 " capacitive touch screen - 1024 x 600 px • Mechanical tamper protection • Wiegand 34/26 • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature 	...
Power supply	12 V DC / 2 A (power adapter not included)	...
Power consumption	≤ 24 W	...
Housing	Compact - Metal	Plastic
Color	Silver + Black	Black
"Index of Protection"	—	IP20
Operation temp	0 °C ... 50 °C	...
Weight	1.34 kg	0.024 kg
Dimensions	117 x 290 x 35 mm (without bracket)	39 x 25 x 23 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	Hikvision	BleBox
SAP Code	302917212	...
Guarantee	3 years	2 years