

	<a href="#">Switch RG-ES08G 8-PORT REYEE</a>	<a href="#">CYLINDRICAL MAGNETIC CONTACT S-2-BR SATEL</a>	<a href="#">IP VANDALPROOF CAMERA DS-2CD2143G2-I(2.8MM) ACUSENSE - 4 Mpx 2.8 mm Hikvision</a>
			
	400.75 SEK 400.75 SEK	67.39 SEK 67.39 SEK	2531.00 SEK 2531.00 SEK
Standard	...	...	TCP/IP
LAN ports	8 x (RJ45) 10/100/1000 Mbps	...	...
Detection	...	Opening the door or window	...
Sensor	...	...	1/3 " Progressive Scan CMOS
Management	—	...	...
Maximum reed switched voltage	...	20 V	...
Matrix size	...	...	4 Mpx
Maximal switched current	...	20 mA	...
Scanning system	...	...	Progressive
Transmission speed	10/100/1000 Mbps - Gigabit Ethernet	...	...
Make distance	...	28 mm	...
Switching capacity	16 Gb/s	...	...
Break distance	...	40 mm	...
Main features	...	Tamper signaling	...
Forwarding rate	11.904 Mpps	...	...
MAC addresses table	4k	...	...
Certificates	RoHS, CE	...	...
Number of fan coolers	—	...	...
Resolution	...	...	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	...	2.8 mm
Permissible relative humidity	10 % ... 90 % (non-condensing)	...	...
View angle	...	...	• 103 ° (manufacturer data) • 97 ° (our tests result)
Range of IR illumination	...	...	30 m
RS-485 interface	...	...	—
Image compression method	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	...	—
Audio	...	...	—
Memory card slot	...	...	Micro SD memory cards up to 256GB support (possible local recording)
Main stream frame rate	...	...	25 fps @ 4 Mpx
Network interface	...	...	10/100 Base-T (RJ-45)
Network protocols	...	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS, PPPoE
WEB Server	...	...	Built-in
Max. number of on-line users	...	...	6
ONVIF	...	...	18.12

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	...	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a> • iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a>
Default admin user / password	...	...	admin / -
Default IP address	...	...	192.168.1.64
Web browser access ports	...	...	80
PC client access ports	...	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	...	8000
Port ONVIF	...	...	80
RTSP URL	...	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main features	...	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• RESET button</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Day/night mode</li> <li>• ICR filter - IR illuminators support</li> <li>• WB - White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, face detection</li> </ul>
Power supply	9 V DC / 600 mA (power adapter included)	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 400 mA</li> </ul>
Power consumption	≤ 6.5 W	...	<ul style="list-style-type: none"> <li>≤ 6.5 W @ PoE (802.3af)</li> <li>≤ 5 W @ 12 V DC</li> </ul>
Housing	...	...	Dome, Metal
Vandal-proof	...	...	IK10
"Index of Protection"	...	...	IP67
Color	...	Brown	White
Operation temp	0 °C ... 40 °C	...	-30 °C ... 60 °C
Weight	0.13 kg	0.03 kg	0.54 kg
Dimensions	144 x 85 x 34 mm	Ø 9.8 x 28 mm	Ø 111 x 85 mm
Supported languages	...	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	RUIJIE / REYEE	SATEL	Hikvision
SAP Code	...	...	311313649

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	2 years	3 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00