

| | | |
|-----------------------------------|--|---|
| | DOOR CONTROLLER ACCO-KP2 SATEL | ELECTRICAL INSTALLATION BOX INTO THERMAL INSULATION KUZ-VO-KB KOPOS |
| |  |  |
| | 1260.78 SEK 1260.78 SEK | 328.42 SEK 328.42 SEK |
| Input lines | 12 | ... |
| Output lines | 12 | ... |
| Number of sections | ... | 1, 2 |
| "Index of Protection" | ... | IP30 / IP44 |
| Operation modes | <ul style="list-style-type: none"> • Autonomous operation, • Work in the ACCO/ACCO NET system | ... |
| Voltage insulation | ... | ~ 400 V |
| Outputs rating | <ul style="list-style-type: none"> • 50 mA / 12 V DC - (OUT 1-12) • 0.5 A / 12 V DC - (+G 1-4) | ... |
| Relay switching voltage | 250 V AC, 30 V DC | ... |
| Relay contacts load | 8 A | ... |
| Communication | RS-485 | ... |
| Material | ... | Non-halogen plastic |
| Color | ... | Light gray |
| Thickness of the insulating layer | ... | 80 ... 140 mm |
| Mounting holes distance | ... | 60 mm, 71 mm |

| | | |
|---------------|---|--|
| Main features | <ul style="list-style-type: none"> • 5 programmable input lines NO/NC • Additional dedicated inputs for connecting readers, monitoring the presence of readers, and connecting the tamper circuit • power input • 2 programmable low-current output lines OC • Additional outputs dedicated to connecting readers • Relay output to control the electromagnetic lock, gate controllers or other devices that activate the door • 4 power outputs 12 V/0.5 A • Support for single door with entry and exit authorization, • 1024 users • Possibility to add different privileges to the users • Identification: Card and/or PIN, Dallas iButton • History of 24 576 events • Recording of information about Time&Attendance • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Holiday access schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Scheduled door locking and unlocking • Limiting of accesses • Compliance with the EM-MARIN, Wiegand 26-56bit, DALLAS protocol • micro USB socket - The ability to firmware upgrade • Its own clock with battery backup • LED indicators displaying the device's operating status • APS power socket - SATEL power adapter (not included) | <ul style="list-style-type: none"> • for insulating systems • temperature range : -25 °C ... 60 °C • flammability index : 850 °C • adjustable depth of the box • Guides for attaching the TS35 rail • Mounting screws, opening lid, rubber gasket - included |
| Power supply | 12 V DC | ... |



| | | |
|-------------------------------|---|--|
| Current consumption | <ul style="list-style-type: none"> • 110 mA (Standby mode) • 480 mA (operation) | ... |
| Permissible relative humidity | 93 % ± 3 % | ... |
| Weight | 0.11 kg | 0.558 kg |
| Dimensions | 142 x 71 x 17 mm | 196 x 156 x 86 ... 146 mm (box) 210 x 170 x 12 mm (cover) |
| Manufacturer / Brand | SATEL | KOPOS |
| Guarantee | 2 years | 2 years |