




	AUTOTRANSFORMER ATS-110/230V	DUAL SMART LIGHT TOUCH SWITCH ATLO-TB2- TUYA Wi-Fi, Tuya Smart	QUAD SMART LED LIGHTING CONTROLLER ATLO-SW4-TUYA Wi-Fi, Tuya Smart
			
	59.04 USD 59.04 USD	10.95 USD 10.95 USD	21.40 USD 21.40 USD
Adapter type	Transforming
Power voltage	115 V AC
Application	...	Works with lighting - switching on/off	switching devices on/off
Number of channels	4
Output voltage	230 V AC
Maximal load	0.4 A
Nominal power	100 VA
Rated voltage	...	100 ... 240 V AC, 50 / 60 Hz	...
Length of the cables	0.65 m
Power supply	100 ... 240 V AC, 50 / 60 Hz
Maximal total load	4 x 150W W
Total maximal current	4 x 2.5 A
Maximum power	...	300 W (for each output)	...
Protection type	Fuse 0.8 A
Number of inputs	4
Rated current	...	max. 10 A	...
Number of buttons	...	2 (touch)	...
Number of outputs	...	2	4
Connector type	...	screw terminals	screw terminals
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth
Radio communication range	< 100 m (open area)
Mobile phones support	...	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS

Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication • Backlit, touch control panel • The product does not fit standard mounting boxes with a diameter of 60 mm 	<ul style="list-style-type: none"> • Local control by physical button , Tuya Smart : • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • The ability to set the default status of the device after a power failure
Housing	...	Plastic + Acrylic glass (plexiglass)	Plastic
"Index of Protection"	IP20
Color	...	White	White
Operation temp	...	-20 °C ... 50 °C	-10 °C ... 40 °C
Permissible relative humidity	...	≤ 80 %	...
Weight	0.75 kg	0.134 kg	0.03 kg
Dimensions	121 x 71 x 45 mm	86 x 86 x 34 mm	43 x 39 x 22 mm
Guarantee	2 years	2 years	2 years