




	DEMONSTRATION KIT PDK-2-STK ROGER	IP CAMERA DS-2CD1027G2H-LIU(2.8MM) ColorVu - 1080p Hikvision	ANGULAR PLUG LE-50105 230 V 16 A LEGRAND
			
	745.64 CHF 745.64 CHF	172.66 CHF 172.66 CHF	3.83 CHF 3.83 CHF
Standard	...	IP	...
Rated voltage	230 V / 50 Hz
Maximal current load	16 A
Grounding	✓
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p	...
Electrical cable	max. 3 x 2.5 mm ²
Cable terminals	screw terminals
Sensor	...	1/2.8 " Progressive Scan CMOS	...
Plug type	CEE 7/6
Lens	...	2.8 mm	...
View angle	...	115 °	...
White light LED illuminator range	...	30 m	...
Range of IR illumination	...	30 m	...
Memory card slot	...	—	...
Content of the case	<ul style="list-style-type: none"> • Access controller MC16-PAC-8 • micro SD memory card with configuration data • RFID readers MCT48M - 2 pcs • Administrator reader RUD-3 • Communication interface RUD-1 • IOS-1 sockets and simulators • A set of 10 13.56 MHz S50 Classic 1k proximity cards • Ethernet network cable - 2 x RJ45 • micro SD Memory Card Reader • USB cable
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network 	...
Main stream frame rate	...	20 fps @ 1080p	...
Interface	...	10/100 Base-T (RJ-45)	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	6	...
ONVIF	...	✓	...

Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles 	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	...	192.168.1.64	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	...	8000	...
Port ONVIF	...	80	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 450 mA 	...
Power consumption	...	<ul style="list-style-type: none"> • ≤ 6.5 W @ PoE • ≤ 5.4 W @ 12 V DC 	...
Housing	...	Compact, Metal	...
Color	...	White	Gray
"Index of Protection"	...	IP67	...
Mechanical protection class	...	—	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	4.35 kg	0.29 kg	0.032 kg
Dimensions	465 x 340 x 170 mm	173 x 70 x 68 mm	84 x 37 x 42 mm
Supported languages	...	Polish, Ukrainian	...
Manufacturer / Brand	ROGER	Hikvision	LEGRAND
SAP Code	...	311325408	...
Guarantee	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00