




	IP SPEED DOME CAMERA OUTDOOR DS-2SE7C124IW-AE(32X/4)(S5) ACUSENSE - 1080p 4.8 ... 153 mm Hikvision	MAINS SOCKET TESTER UT-07A-EU UNI-T	BOX FOR FLUSH-MOUNTED CONNECTIONS FOR HOUSEHOLD APPLIANCES PK-AGD/1/EPN Elektro-Plast
			
	19991.65 SEK 19991.65 SEK	78.24 SEK 78.24 SEK	65.96 SEK 65.96 SEK
Rated voltage	...	230 V AC	...
Standard	TCP/IP
Number of terminals	5 pcs : 2 x 2.5 mm ² - screw terminals
Sensor	<ul style="list-style-type: none"> • Camera PTZ : 1/2.8 " Progressive Scan CMOS • Camera 2 : 1/2.8 Progressive Scan CMOS
Operation temp	...	0 °C ... 40 °C	...
Main features	...	<ul style="list-style-type: none"> • Phase conductor position test • Signaling a lack of grounding • Signaling phase failure • Signaling a lack of a neutral wire • Signaling of phase and ground swap • Signaling of phase and ground swap and a lack of grounding 	<ul style="list-style-type: none"> • Claw or screw mounting • Cover fastened with latches • Flat housing profile : 21 mm
Matrix size	<ul style="list-style-type: none"> • Camera PTZ : 2.1 Mpx • Camera 2 : 3.7 Mpx
Material	Plastic
Resolution	2560 x 1440 - 3.7 Mpx (Camera 2) , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Scanning system	Progressive
Lens	<ul style="list-style-type: none"> • Camera PTZ : 4.8 ... 153 mm F1.2 • Camera 2 : 4.0 mm F1.6
View angle	<ul style="list-style-type: none"> • Camera PTZ : 58 ° ... 2.1 ° (manufacturer data) 58 ° ... 2.6 ° (our tests result) • Camera 2 : 79 ° (manufacturer data) 70 ° (our tests result)
Optical zoom	x 32
Digital zoom	x 16
Range of IR illumination	200 m
Video output	—
Preset rotation speed	<ul style="list-style-type: none"> • 240 °/s (horizontal) • 200 °/s (vertical)

Rotation speed (manual control)	0.1 °/s ... 160 °/s (horizontal) 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range	360 ° - continuous
Vertical rotation range	-15 ° ... 90 °
RS-485 interface	—
Number of presets	300
Horizontal scan	✓
Route settings	4
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	2 / 1
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Audio detection • Speaker built-in - Alarm siren • Bi-directional audio streaming support • Digital Noise Reduction
Main stream frame rate	<ul style="list-style-type: none"> • Camera PTZ : 25 fps @ 1080p • Camera 2 : 25 fps @ 3.7 Mpx
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
WEB Server	Built-in
Max. number of on-line users	20
ONVIF	✓
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.64
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Camera PTZ - Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Camera PTZ - Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ • Camera 2 - Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/201/ • Camera 2 - Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/202/



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • Sharpness - sharper image outlines • Configurable: brightness, contrast, saturation • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Privacy zones • Motion Detection • Intelligent 3D Positioning System • Intelligent Object Tracking • Active deterrence function - Light and sound alarm • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, advanced face capture features - detection of up to 5 faces simultaneously • The camera is equipped with a built-in heater with a thermostat
Power supply	<ul style="list-style-type: none"> • Hi-PoE, • 24 V AC / 5 A (power adapter included)
Power consumption	max. 60 W
Housing	Speed Dome, Metal
Color	White	...	White
Operation temp	-30 °C ... 65 °C
"Index of Protection"	IP66	IP40	IP40
Weight	6.2 kg	0.08 kg	0.06 kg
Dimensions	Ø 220 x 373 mm (without bracket)	65 x 65 x 72 mm	82 x 82 x 45 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	Hikvision	UNI-T	Elektro-Plast Nasielsk
SAP Code	301316793
Guarantee	3 years	2 years	2 years