






	RFID PROXIMITY CARD WITH MODIFIED UID EMC-4	RUBBER MAT MB-GUM/50	KIT ZSW-01 SUPLA ZAMEL	ELECTRIC CABLE DY-2.5-BK/750V	OVERVOLTAGE LIMITER AXON-POWER/DIN
					
	3.44 EUR 3.44 EUR	6.31 EUR 6.31 EUR	423.25 EUR 423.25 EUR	0.44 EUR 0.44 EUR	35.62 EUR 35.62 EUR
Standard	Unique EM 125kHz
Compatibility	EM4100/4102
Support	SUPLA
Possibility of programming the serial number (ID)	✓
Ability to write to internal memory	—
Maximal voltage	250 V AC / 50 Hz
In section	100 m . Price for 1m when buying a whole roll	...
Rated current	10 A
Inner conductor	2.5 mm ² - Cu wire	...
Material	...	SBR granulate + polyurethane binder
Serial Number overprint	—
Protection level Up L/PE, N/PE	≤ 1.3 kV
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Rated voltage	450 / 750 V	230 V AC / 50 Hz
Protection level Up L/N	≤ 3 kV
Outer coating	Ø 3.3 mm - PVC	...
Mobile phones support	<ul style="list-style-type: none"> The SUPLA free application on Android The SUPLA free application on iOS
Nominal discharge current (L/N, L/PE, N/PE)	4 kA - 8/20 μs
Coating color	Black	...
Maximum stroke current (L/N, L/PE, N/PE)	10 kA 8/20 μs (type 2)
Operation state indication	✓
Connectors type	2 x terminals
Main features	Can be programmed using the RUD-1 + PRT-32EM	<ul style="list-style-type: none"> Rough structure Granule fraction : 0.5 ... 4 mm Insulation High fatigue strength of the material Weatherproof Very easy and quick assembly 	<ul style="list-style-type: none"> Control from a Web browser, Local control by physical button, schedule, timer, remote access, voice control, Possibility to manually program scenarios from the built-in API
Housing	Plastic	...	<ul style="list-style-type: none"> Plastic DIN, TS-35 rail mounting
Color	...	Black	Green
Manufacturer / Brand	ROGER	...	ZAMEL
Maximal outputs load	350 W
Number of elements	7 6 1

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Application	...	<ul style="list-style-type: none"> • Area covering, • Soundproofing 	roller shutters, roof windows, awnings, drop-down screens, curtains swing gates, sliding gates, garage gates, doors
Power voltage	230 V AC 24 V AC/DC
Relay maximal load	2 x 5 A @ 250 V AC 5 A @ 250 V AC
Number of inputs	2 pcs 2
Number of outputs	1 pcs (Motor) 1
Connector type	screw terminals screw terminals screw terminals
"Index of Protection"	IP20 IP20
Operation temp	-10 °C ... 55 °C -20 °C ... 50 °C
Weight	0.006 kg	2.4 kg	0.410 kg 0.030 kg 0.034 kg	...	0.075 kg
Dimensions	86 x 55 x 1 mm	500 x 500 x 10 mm	47 x 47 x 20 mm 47 x 47 x 20 mm	...	86 x 58 x 35 mm
Guarantee	2 years	...	2 years	2 years	2 years