



	ELECTRICAL INSTALLATION BOX INTO THERMAL INSULATION KUZ-VO-KB KOPOS	ACCESS CONTROLLER ASI1212F DAHUA
		
	28.62 EUR 28.62 EUR	229.00 EUR 229.00 EUR
Cards support	...	13.56 MHz S50
Reading distance of prox-keys	...	1 ... 3 cm
Number of sections	1, 2	...
Keyboard built-in	...	—
Autonomous operation	...	✓
Battery backup support	...	—
Voltage insulation	~ 400 V	...
Input lines	...	3
Output lines	...	3
Identification time	...	< 1.5 s
Communication	...	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	✓
Network interface	...	10/100 Base-T
Default IP address	...	192.168.1.108
Material	Non-halogen plastic	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Color	Light gray	...
USB	...	—
Memory card slot	...	—
Internal memory	...	Support storage of 150 000 records
Thickness of the insulating layer	80 ... 140 mm	...
Power supply	...	12 V DC / 1 A
Mounting holes distance	60 mm, 71 mm	...

Main features	<ul style="list-style-type: none"> • for insulating systems • temperature range : -25 °C ... 60 °C • flammability index : 850 °C • adjustable depth of the box • Guides for attaching the TS35 rail • Mounting screws, opening lid, rubber gasket - included 	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC
"Index of Protection"	IP30 / IP44	—
Operation temp	...	-10 °C ... 45 °C
Permissible relative humidity	...	5 ... 90 % (non-condensing)
Dimensions	196 x 156 x 86 ... 146 mm (box) 210 x 170 x 12 mm (cover)	115 x 115 x 32 mm
Weight	0.558 kg	0.22 kg
Supported languages	...	English
Manufacturer / Brand	KOPOS	DAHUA
Guarantee	2 years	3 years