



	ROUTER RG-EG210G-P 8 PoE REYEE	ACCESS POINT +ROUTER ARCHER-VR400 VDSL / ADSL 300 Mbps + 867 Mbps
		
	378.88 AUD 378.88 AUD	131.20 AUD 131.20 AUD
Frequency range	...	<ul style="list-style-type: none"> • 2.4 GHz, • 5 GHz
LED indicators	Status, Link/Act	...
Port USB	—	...
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
Power supply PoE	Power output - LAN ports : PoE (802.3af/at) max. 70 W (total)	...
LAN ports	<ul style="list-style-type: none"> • 8 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45) 	3x RJ-45 (10/100 Mbps, Auto MDI/MDX) 1x RJ-45 (10/100/1000 Mbps, Auto MDI/MDX)
WAN interface	<ul style="list-style-type: none"> • 1 x WAN 10/100/1000 Mbps (RJ-45) 	1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2
Transmitter power	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee	...
Baud rates	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	✓	✓
Firmware update	✓	✓
DDNS	✓	✓

Protections	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping 	<ul style="list-style-type: none"> • LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL • WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser 	Web browser
Power consumption	≤ 80 W (at full load)	...
Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • 1 x Port USB 2.0 • The DSL line splitter included
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	max. 90 % (max)
Power supply	100 ... 240 V AC, 50 / 60 Hz	12 V DC / 1.5 A (power adapter included)
Weight	0.53 kg	0.32 kg
Dimensions	207 x 109 x 27 mm	216 x 125 x 32 mm
Manufacturer / Brand	RUIJIE / REYEE	TP-LINK
Guarantee	2 years	2 years