



	CRIMPING TOOL HT-202B	ROUTER WIFI RG-EG105GW(T) Wi-Fi 5, 867 Mbps + 400 Mbps REYEE
		
	9.37 EUR 9.37 EUR	148.40 EUR 148.40 EUR
Frequency range	...	2.4 GHz, 5 GHz
Material	Metal / PET	...
Application	<ul style="list-style-type: none"> • Telephone connectors for the AWG 22-26 cable, • Insulated connectors for the AWG 22-26 cable, • Uninsulated connectors for the AWG 10-22 cable 	...
Antenna type	...	2x2 MIMO - built-in <ul style="list-style-type: none"> • 3 dBi @ 2.4 GHz • 4 dBi @ 5 GHz
Standards	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac, Wi-Fi 5
Baud rates	...	867 Mbps @ 5 GHz + 400 Mbps @ 2.4 GHz
LAN ports	...	<ul style="list-style-type: none"> • 1 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)
WAN interface	...	<ul style="list-style-type: none"> • 1 x WAN x 10/100/1000 Mbps (RJ-45)
LED indicators	...	Status, Link/Act, Mesh
DDNS	...	✓
DHCP server	...	✓
Port USB	...	✓
Firmware update	...	✓
Power supply PoE	...	—
Protections	...	<ul style="list-style-type: none"> • TCP scan blocking • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NATP • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks

Management interface	...	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reyeeye application • Remote management • Web browser
Mobile phones support	...	<p>Android: Free application Ruijie Reyeeye</p> <p>iOS (iPhone): Free application Ruijie Reyeeye</p>
Main features	...	<ul style="list-style-type: none"> • Support for Reyeeye Mesh technology • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button
Power supply	...	12 V DC / 1.5 A (power adapter included)
Power consumption	...	≤ 15 W
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.215 kg	0.29 kg
Dimensions	185 x 59 x 14 mm	119 x 119 x 29 mm
Manufacturer / Brand	...	RUIJIE / REYEE
Guarantee	2 years	2 years