



	ROUTER TL-WR841N 300 Mbps TP-LINK	CHARGER BAT- RECHARGE/X4 XTAR
		
	18.84 EUR 18.84 EUR	36.22 EUR 36.22 EUR
Frequency range	2.4 GHz ... 2.4835 GHz	...
Antenna type	2 x 5 dBi	...
Standards	IEEE 802.11 b/g/n	...
Baud rates	300 Mbps	...
Processor	Atheros	...
Modulation type	CCK, OFDM, BPSK, QPSK	...
LAN ports	1 x 10/100 Mbps Uplink 4 x 10/100 Mbps LAN	...
LED indicators	Power, System, LAN, WLAN, Act/Link (4 x Ethernet)	...
Receiver sensitivity	<ul style="list-style-type: none"> • 270M: -68dBm@10% PER • 130M: -68dBm@10% PER • 108M: -68dBm@10% PER • 54M: -68dBm@10% PER • 11M: -85dBm@8% PER • 6M: -88dBm@10% PER • 1M: -90dBm@8% PER 	...
DDNS	<ul style="list-style-type: none"> • No-IP • DynDNS • Comexe 	...
DHCP server	✓	...
Firmware update	✓	...
Battery type	...	<ul style="list-style-type: none"> • Li-Ion 3.6 / 3.7 V - ICR / IMR / INR, 14500, 14650, 16340, 17335, 17500, 17670, 18350, 18490, 18500, 18650, 18700, 20700, 21700, 22650, 25500, 26650, • Ni-MH, Ni-Cd 1.2 V - AAAA / AAA / AA / A / C
Operation modes	Router, Bridge WDS	...
Protections	64/128/152-bit WEP, WPA/WPA2 Table of access / access-deny according to MAC addresses of client cards Internet access filtering via filters of IP addresses, MAC addresses and ports of TCP/IP protocol	...

Management interface	Web browser	...
Transmitter power	max. 20 dBm	...
Battery charging current	...	0.5 A @ 4 pcs , 1 A @ 4 pcs , 2 A @ 2 pcs
LED indicator	...	—
LCD display	...	✓
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	max. 90 % (non-condensing)	...
Main features	<ul style="list-style-type: none"> • MAC address cloning • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch 	<ul style="list-style-type: none"> • The LCD display informs about the charging capacity, cell voltage, charging current and percentage of battery charge, • Supports protected PCM/PCB batteries in sizes 20700/21700, • Deeply discharged cell reactivation function, • Power Bank (5V, max. 1A) function • Charging Li-ion batteries controlled by a three-stage processor TC/CC/CV charging process • charging Ni-MH batteries with the CC method • 4 independent charging channels • End of charge voltage : 4.2 V @ Li-Ion, 1.45 V @ NiMH • Short-circuit protection • Protection against reverse polarity connection • Overload protection • Overvoltage protection • Overcharge protection
Power supply	9 V DC / 600 mA (power adapter included)	<ul style="list-style-type: none"> • 100 V ... 240 V AC • 5 V DC / 2.1 A @ Micro USB-B socket (power adapter not included)
Weight	0.170 kg	0.27 kg
Dimensions	192 x 130 x 33 mm	<ul style="list-style-type: none"> • 118 x 143 x 38 mm • Power cord : 120 cm
Manufacturer / Brand	TP-LINK	XTAR
Guarantee	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00