








	CABLE PINS/RJ-TTL SATEL	HDD ENCLOSURE Y-3035 UNITEK	TURNBUCKLE VANT-8/PL	THIMBLE FOR LINE KAUSZA-5	ACCESS POINT 4G LTE +ROUTER TL-MR100 2.4 GHz 300 Mbps TP-LINK	TV OR MONITOR MOUNT AX-TYTAN-MAXXIM	THERMALLY CONDUCTIVE ADHESIVE TERM-GLUE/120 TUBE 120 g AG TERMO PASTY
							
	13.63 EUR 13.63 EUR	31.48 EUR 31.48 EUR	2.67 EUR 2.67 EUR	0.25 EUR 0.25 EUR	61.88 EUR 61.88 EUR	23.65 EUR 23.65 EUR	20.81 EUR 20.81 EUR
Frequency range	2.4 GHz
Application	Steel lines	Steel lines Ø 5 mm
Support	ETHM-1, VERSA
Package	Tube 120 g
Material	Metal	Metal
Length of the cable	0.3 m
Supported hard drives	...	1 x SATA III, 2.5 " / 3.5 "
Outputs	...	1 x USB 3.1, max. 5 Gb/s
Operation state indication	...	LED diodes
Antenna type	WiFi embedded , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna
Standards	IEEE 802.11 b/g/n
Mounting standard	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	...
Screen size range	36 " ... 70 "	...
Bearing capacity	50 kg	...
Housing	...	Desktop, Plastic
Distance from mounting surface	75 ... 400 mm	...
Color	Black	White
Tilt adjustment	0 ° ... 10 °	...
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps
Horizontal rotation	-90 ° ... 90 °	...
Rotation in the plane of the screen	± 3 °	...
LAN ports	• 1 x 10/100 Mbps - LAN/WAN • 1 x 10/100 Mbps - LAN
Receiver sensitivity	• 11g 54M : -74 dBm • 11n HT20 : -71 dBm • 11n HT40 : -68 dBm
Transmitter power	< 20 dBm
LED indicators	Power, WAN, WLAN, LAN, GSM
Network type	• 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz
LTE	✓
QSS	—
WDS	—
DDNS	• DynDNS • No-IP
DHCP server	✓
Firmware update	✓
Protections	• WEP 64/128-bit, WPA/WPA2, WPA- PSK/WPA2-PSK • SPI network firewall • IP-MAC Binding
Management interface	Web browser
Operation modes	• Router, • Router 4G LTE

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> Screw diameter 8 mm Work load 140 kg Corrosion resistance 	Corrosion resistance	<ul style="list-style-type: none"> Number of users - max. 32 SIM socket - The nanoSIM cards support WPS/RESET button Enable/disable wireless network WMM (Wi-Fi Multimedia) Wireless Network Schedule Wireless transmission statistics The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss Static / dynamic routing PPTP L2TP Remote management DHCP client list Port forwarding : UPnP, DMZ Guest Network - a separate and secure network for guests
Power supply	...	12 V DC / 2 A (power adapter included)	9 V DC / 0.85 A (power adapter included)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.05 kg	0.2 kg	0.105 kg	0.009 kg	0.184 kg	4.52 kg	...
Dimensions	...	183 x 117 x 35 mm	170 x 21 x 12 mm	41 x 27 x 9 mm	155 x 114 x 34 mm	640 x 420 x (75 ... 400) mm	...
Manufacturer / Brand	SATEL	UNITEK	TP-LINK	...	AG TERMOPASTY
Guarantee	2 years	2 years	2 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00