

	AC POWER SUPPLY ADAPTER AWT-027	CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P/RGBW 12 mm ORNO	SET OF LED LUMINAIRES ZSO-01/3000 ZAMEL	HUB USB 3.0 H1208A	KIT ZSW-01 SUPLA ZAMEL
					
	11.02 EUR 11.02 EUR	1.35 EUR 1.35 EUR	75.74 EUR 75.74 EUR	5.14 EUR 5.14 EUR	417.90 EUR 417.90 EUR
Adapter type	Transforming
Number of power outputs	...	2 pcs
Support	SUPLA	...	SUPLA
Strip width	...	12 mm
Connectors	• 1 x plug - USB-A • 4 x socket - USB-A	...
Length of the cable	...	140 mm	...	18 cm	...
USB standard	3.0	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Maximal power voltage	...	48 V
Mobile phones support	• The SUPLA free application on Android • The SUPLA free application on iOS	...	• The SUPLA free application on Android • The SUPLA free application on iOS
Output voltage	• 11.5 V AC, wires : Yellow - Blue, • 14 V AC, wires : Yellow - Red
Maximal load	• 0.8 A @ 11.5 V AC, • 0.6 A @ 14 V AC
Length of the cables	1 m + 1.5 m
Application	Door lock (strike) 11.5V / 14V AC
Protection type	Overheat 130 °C
Main features	• Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API	Solid workmanship	• Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API
Housing	...	Plastic	Plastic	...	Plastic
Color	...	White	Green
Manufacturer / Brand	PULSAR	ORNO	ZAMEL	UNITEK	ZAMEL
Guarantee	2 years	2 years	2 years	2 years	2 years
Maximal outputs load	350 W
Light color	Warm - 3000 K Warm - 3000 K
Illumination angle	120 ° 120 °
Application	...	Works with LED lighting RGBW	Lighting control	...	roller shutters, roof windows, awnings, drop-down screens, curtains swing gates, sliding gates, garage gates, doors
Seating depth of the luminaire	38 mm 38 mm
Montage hole diameter	Ø 75 mm ... 80 mm Ø 75 mm ... 80 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Relay maximal load	2 x 5 A @ 250 V AC 5 A @ 250 V AC
Power voltage	230 V AC	...	24 V DC 24 V AC	...	230 V AC 24 V AC/DC
Number of inputs	1 pcs 1	...	2 pcs 2
Number of outputs	1 pcs	...	1 pcs (Motor) 1
Current consumption	350 lm / 3.5 W 350 lm / 3.3 W
Connector type	screw terminals screw terminals screw terminals	...	screw terminals screw terminals screw terminals
"Index of Protection"	...	—	IP20 IP44	...	IP20 IP20
Operation temp	-10 °C ... 55 °C	...	-10 °C ... 55 °C -20 °C ... 50 °C
Number of elements	8 3 3	...	7 6 1
Material	Plastic
Weight	0.58 kg	0.002 kg	0.079 kg 0.068 kg 0.019 kg	0.03 kg	0.410 kg 0.030 kg 0.034 kg
Dimensions	80 x 48 x 63 mm	140 x 15 x 5 mm	78 x 73 x 40 mm 78 x 72 x 35 mm Ø 105 x 7 mm	88 x 17 x 9 mm	47 x 47 x 20 mm 47 x 47 x 20 mm