





	IP CAMERA DS-2CD1347G2H-LIU(2.8MM) Smart Hybrid Light - 4 Mpx Hikvision	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	TELECOMMUNICATION ENCLOSURE ABOX-XL2 308 x 228 x 130 mm ATTE
			
	199.34 EUR 199.34 EUR	29.53 EUR 29.53 EUR	68.70 EUR 68.70 EUR
Material	Plastic (ABS)
Standard	IP
Rated voltage	...	230 V AC / 50 Hz	...
Nominal load current	...	10 A (total)	...
Mounting plate	203 x 285 mm - Steel galvanized
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...
Number of outlets	...	8 grounded outlets 10A/250V	...
Resolution	2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Automatic delayed fuse	...	✓	...
Sensor	1/3 " Progressive Scan CMOS
Nominal stroke current	...	2 kA (L/N) - 8/20 µs	...
Lens	2.8 mm
Maximum stroke current	...	6.5 kA (L/N) - 8/20 µs	...
Main features	<ul style="list-style-type: none"> • Box casing designed to wall mounting • Raster module mounting system (compatible with ATTE devices) • The enclosure is equipped with 6 cable entries with glands in the arrangement 5 x M16 + 1 x M20 • Place for battery : 7 Ah • "Index of Protection" : IP56
View angle	96 °
Leak current	...	< 0.5 mA	...
Response time	...	< 25 ns	...
White light LED illuminator range	30 m
Switch	...	two-way, with light indication	...
Housing external dimensions	308 x 228 x 130 mm
Range of IR illumination	30 m
Length of the cable	...	2.9 m	...
Memory card slot	—
Internal dimensions	300 x 220 x 120 mm
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction
Main stream frame rate	20 fps @ 4 Mpx 25 fps @ 1080p
Interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
ONVIF	✓
Main features	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • Possibility to turn off the LED illuminator • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Sharpness - sharper image outlines • video tampering • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles)
Mobile phones support	<ul style="list-style-type: none"> • Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE • ≤ 6 W @ 12 V DC
Housing	Dome, Metal + Plastic	RACK 19", 1U, Plastic - non-flammable	...
Color	White	...	Gray RAL7035
"Index of Protection"	IP67
Mechanical protection class	—
Operation temp	-30 °C ... 60 °C
Weight	0.39 kg	0.61 kg	1.28 kg
Dimensions	Ø 110 x 93 mm	445 x 54 x 55 mm	...


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	English, Ukrainian
Manufacturer / Brand	Hikvision	...	ATTE
SAP Code	311325148
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00