



	EXTENDER ETHERNET VIA UTP CABLE EA-EOU101 COP	ACCESS CONTROLLER PR621 ROGER	UNIVERSAL MIDDLE CLAMP PV-KS/50/B FOR SOLAR PANELS	ACCESS CONTROLLER ASC2202B-D DAHUA
				
	78.45 EUR 78.45 EUR	107.95 EUR 107.95 EUR	0.74 EUR 0.74 EUR	269.02 EUR 269.02 EUR
LAN ports	1 pcs RJ45
Number of served transitions	2 (two-way)
Material	Aluminum	...
Relay contacts load	...	1.5 A / 30 V
Support	DAHUA
Height	21.5 mm	...
Number of supported readers	4 pcs
Hole diameter	9 mm	...
Transmission ports	1 pcs BNC + BNC / UTP converter - cable terminals
Battery backup support	...	—	...	—
Keyboard built-in	...	—
mounting screw	—	...
Input lines	...	3
Transmission speed	10 / 100 Mbps Full Duplex
Output lines	...	3	...	4 pcs - Relay
Transmission range	max. 1000 m
Color	Black	...
Communication	...	<ul style="list-style-type: none"> • RS-485 • RACS (Roger) 	...	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Power supply	12 V DC / 500 mA (power adapter included)	10 ... 15 V DC	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1.4 A
Environment class	...	IV

Main features	<ul style="list-style-type: none"> • Plug & Play • The device uses 1 pair of twisted-pair cable for transmission to 1 IP camera 	<ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PRT series readers support • 1000 indexed users • History of 250 000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface • Function to prevent of multiple use of the same code/card to gain access (anti-passback) 	...	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Default IP address	192.168.0.2
Default admin user / password	admin / - The administrator password should be set at the first start
Operation temp	...	-25 °C ... 60 °C	...	-30 °C ... 60 °C
Permissible relative humidity	...	10 ... 95 % (non-condensing)	...	max. 95 % (non-condensing)
Weight	0.14 kg	0.15 kg	0.026 kg	0.4 kg
Dimensions	120 x 33 x 33 mm	85 x 85 x 27 mm	50 x 36 x 24.5 mm	210 x 106 x 50 mm
Manufacturer / Brand	COP	ROGER	...	DAHUA
Guarantee	2 years	3 years	2 years	3 years