



| | UPS AT-UPS650-LCD 650 VA EAST | TV OR MONITOR MOUNT BRATECK-PLB-CE344 |
|---|--|---|
| |  |  |
| | 64.35 EUR 64.35 EUR | 23.68 EUR 23.68 EUR |
| Nominal power | 390 W | ... |
| Apparent Power | 650 VA | ... |
| Input voltage | 165 V ... 275 V AC | ... |
| Input frequency | 50 / 60 Hz (auto detection) | ... |
| Mounting standard | ... | VESA 75, 100, 200, 200x100, 400, 400x200 |
| Output voltage | 230 V AC \pm 10 % (Approximated Sine Wave) | ... |
| Screen size range | ... | 32 " ... 55 " |
| Bearing capacity | ... | 50 kg |
| Output frequency | 50 / 60 Hz \pm 1 % | ... |
| Transfer time | \leq 10 ms | ... |
| Charging time (recover to 90% capacity) | 8 hours | ... |
| Distance from mounting surface | ... | (manufacturer data) : 1050 ... 1560 mm from ceiling Our tests results : 920 ... 1510 mm from ceiling |
| Battery | 1 pcs - 12V/7Ah | ... |
| Color | ... | Black |
| Tilt adjustment | ... | -15 ° ... 15 ° |
| Horizontal rotation | ... | 360 ° |
| Rotation in the plane of the screen | ... | — |
| Estimated battery operation time | <ul style="list-style-type: none"> • 19 minutes @ 100 W • 6 minutes @ 200 W • 2 minutes @ 300 W | ... |
| Number of outputs | 2 pcs CEE 7/3 (Schuko) | ... |
| Protections | <ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • Overcharge protection • Telephone line filter | ... |
| Operation state indication | <ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, • Sound signaling | ... |

| | | |
|-------------------------------------|--|--------------------|
| Main features | <ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm | ... |
| Application | <ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment | ... |
| Housing type | Tower | ... |
| Operation temp. / Relative humidity | 0 °C ... 40 °C / 20 ... 90 % | ... |
| Weight | 4.3 kg | 5.7 kg |
| Dimensions | 290 x 110 x 145 mm | 1080 x 520 x 60 mm |
| Manufacturer / Brand | EAST | ... |
| Guarantee | 2 years | 2 years |