




	IP CAMERA DS-2CD2T87G2-L(4MM)(C) ColorVu - 8.3 Mpx Hikvision	PATCH PANEL SC MTRJ E2000, LC PP-12/12/2	CABLE PROTECT-M12/10M 10 m
			
	685.81 USD 685.81 USD	6.96 USD 6.96 USD	15.82 USD 15.82 USD
Standard	TCP/IP
Sensor	1/1.2 " Progressive Scan CMOS
Adapter hole dimensions	...	10 x 13 mm	...
Scanning system	Progressive
Cable	M12, 4-pin socket / M12, 4-pin plug - Code A
Matrix size	8.3 Mpx
Length of the cable	10 m
Application	AUTONE mobile recorders and cameras
Main features	Very easy and quick assembly
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	4 mm
View angle	• 88 ° (manufacturer data) • 84 ° (our tests result)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
White light LED illuminator range	60 m
Alarm inputs / outputs	—
Audio	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Main stream frame rate	25 fps @ 8.3 Mpx
Network interface	10/100 Base-T (RJ-45)
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP
WEB Server	Built-in, NVR compliance
Max. number of on-line users	6
ONVIF	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.64
Web browser access ports	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
RS-485 interface	—
Main features	<ul style="list-style-type: none"> • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Configurable Privacy Zones • Motion Detection • Filtering of false alarms based on the recognition of persons and vehicles • Possibility to turn off the LED illuminator • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 700 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 9.5 W @ PoE (802.3af) • ≤ 8.5 W @ 12 V DC
Housing	Compact, Aluminum
Color	White	light gray	...
"Index of Protection"	IP67
Weight	1.18 kg	...	0.26 kg
Dimensions	Ø 105 x 290 mm
Operation temp	-30 °C ... 60 °C
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	Hikvision
SAP Code	311317249
Guarantee	3 years	2 years	2 years