



	<a href="#">CABLE TIE HOLDER PS-5-20X20/W*P50</a>	<a href="#">OVERVOLTAGE LIMITER AXON-RS485 RS-485 SYMMETRIC LINE</a>
		
	3.27 EUR 3.27 EUR	41.61 EUR 41.61 EUR
Rated voltage	...	6 V
Maximal voltage	...	10 V
Rated current	...	0.75 A
In package	<b>50 pcs The price for package</b>	...
Holes dimensions	5 x 2 mm	...
Nominal discharge current (line-line) [C3]	...	25 A - 10/1000 µs
Montage hole diameter	Ø 4 mm	...
Nominal discharge current line-PG [C2]	...	5 kA - 8/20 µs
Protection voltage Up line-line for nominal current [C3]	...	≤ 16 V - 1 kV/µs
Assembly	<ul style="list-style-type: none"> <li>• The bottom layer is equipped with a Scotch tape, ...</li> <li>• Mounting with screws</li> </ul>	...
Color	White	...
Voltage protection level line-PG [C2]	...	≤ 1000 V - 1.2 kV / 50 µs
Serial impedance per line	...	≤ 2 Ω
Bandwidth	...	0 MHz ... 1 MHz
Capacitance line-line	...	50 pF
Capacitance line-PG	...	16 pF
Connectors	...	2x triple screw terminal, removable, 1.5 mm <sup>2</sup> , 3.5 mm distance
Protection parameters compliance	...	Compliance with PN-EN61643-21
Housing	...	Metal, black
Weight	...	0,07 kg
Dimensions	20 x 20 x 8 mm	69 x 32 x 20 mm
Guarantee	2 years	3 years