





	POWER SUPPLY ADAPTER PSC-12010	RFID PROXIMITY CARD WITH MODIFIED UID EMC-4	COAXIAL CABLE RG-174 50 Ω	IP CAMERA BCS-L-TIP58VSR6-A11 - 8.3 Mpx 4K UHD 2.7... 13.5 mm - MOTOZOOM BCS Line
				
	7.76 EUR 7.76 EUR	3.44 EUR 3.44 EUR	0.37 EUR 0.37 EUR	616.16 EUR 616.16 EUR
Standard	TCP/IP
Standard	...	Unique EM 125kHz
Adapter type	Switching
Compatibility	...	EM4100/4102
Power voltage	100 ... 240 V AC
Sensor	1/2.8" Progressive Scan CMOS
Possibility of programming the serial number (ID)	...	✓
Output voltage	12 V DC
Matrix size	8.3 Mpx 4K UHD
In section	100 m . Price for 1m when buying a whole roll	...
Ability to write to internal memory	...	—
Maximal load	1 A
Output power	12 W
Serial Number overprint	...	—
Number of outputs	1 pcs
Power connectors type	2.1/5.5 mm Straight plug
Inner conductor	7 x Ø 0.16 mm Cu Stranded wire	...
Housing type	Plastic
Dielectric	Ø 1.6 mm PE full	...
Shield	—	...
Main features	<ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions 	Can be programmed using the RUD-1 + PRT-32EM
Operation temp	0 °C ... 40 °C
Braid	64 x Ø 0.1 mm Stranded wire Cu	...
Impedance	50 Ω	...
Outer coating	Ø 2.8 mm PVC	...
Cable attenuation at 100m section	17.6 dB @ 30 MHz 21.1 dB @ 50 MHz 28.2 dB @ 100 MHz 21.6 dB @ 146 MHz 80 dB @ 440 MHz 96 dB @ 1000 MHz 240 dB @ 2400 MHz	...
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	2.7 ... 13.5 mm - Motozoom
View angle	<ul style="list-style-type: none"> • 109 ° ... 30 ° (manufacturer data) • 104 ° ... 31 ° (our tests result)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	60 m
Alarm inputs / outputs	1 / 1
Main stream frame rate	25 fps @ 8 Mpx
Network interface	10/100 Base-T (RJ-45)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio input • Audio output • Bi-directional audio streaming support • Audio detection
WEB Server	Built-in
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Max. number of on-line users	20
ONVIF	✓
Mobile phones support	Port no. : 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.108
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
RS-485 interface	—
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms • AFSA - Anti-flicker Self-adaption - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Auto White Balance • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, Smart motion detection (with recognizing people and vehicles)
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 770 mA
Power consumption	≤ 10.5 W
Housing	Compact, Metal
Color	White
"Index of Protection"	IP67	IP67
Operation temp	-30 °C ... 60 °C
Supported languages	Polish, English
Weight	0.12 kg	0.006 kg	...	0.81 kg
Dimensions	50 x 48 x 25 mm	86 x 55 x 1 mm	...	244 x 79 x 76 mm
Manufacturer / Brand	PULSAR	ROGER	...	BCS Line
Guarantee	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00