



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7232HQHI-M2/S(E) 32 CHANNELS Hikvision	ACCESS POINT UNIFI-U6-LITE UBIQUITI
		
	310666.67 HUF 310666.67 HUF	56176.19 HUF 56176.19 HUF
Frequency range	...	2.4 GHz / 5 GHz
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Video inputs	32 pcs BNC	...
Antenna type	...	2x2 MIMO, 2.4 GHz - 2.8 dBi / 5.0 GHz - 3 dBi, Integrated - 2 x Omnidirectional antenna
Video outputs	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265 / H.265+ / H.264 / H.264+	...
Standards	...	<ul style="list-style-type: none"> • IEEE 802.11a, • IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n, • IEEE 802.11ac, • IEEE 802.11ax
Baud rates	...	<ul style="list-style-type: none"> • 1201 Mbps @ 5 GHz, • 300 Mbps @ 2.4 GHz
Protections	...	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
LAN ports	...	1 x 10/100/1000 Mbps
Operating system	...	UniFi WiFi Enterprise System
Transmitter power	...	<ul style="list-style-type: none"> • 20 dBm @ 2.4 GHz (max) • 20 dBm @ 5.0 GHz (max)
Power supply PoE	...	Ubiquiti Passive PoE
Power consumption	...	12 W

Main features	...	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • UniFi WiFi Enterprise System • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions
Operation temp	...	-30 °C ... 60 °C
Permissible relative humidity	...	5 % ... 95 %
Image records resolutions	<ul style="list-style-type: none"> • AHD : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-CVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...
Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps IP 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	32 x HD-TVI / AHD / HD-CVI / PAL / IP + 8 x IP	...
Recording modes	Manual, Motion Detection, Schedule	...
Supported hard drives	2 x 10 TB SATA	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 16 cameras in the same time	...
Network interface	1 x RJ-45 - 10/100/1000 Base-T	...
Bitrate	32 ... 6144 kbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • Android: Free application Hik-Connect	...
Default IP address	DHCP or 192.168.1.64	...
Default admin user / password	admin / -	...
Web browser access ports	80	...
PC client access ports	554 RTSP, 8000	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream	...
Alarm inputs / outputs	—	...
PTZ control	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision	...
Motion Detection	2.0	...
Main features	• DVR from the AcuSense series • Intelligent image analysis : intrusion, crossing the line (tripwire), Deep Learning technology • Filtering of false alarms based on the recognition of persons and vehicles • Motion detection with human/vehicle silhouette recognition	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 5 A (power adapter included)	• PoE (802.3af), • 44 ... 57 V DC / 0.25 A - PoE Adapter (not included)
Color	Black	...
Weight	2.12 kg	0.33 kg
Dimensions	380 x 330 x 52 mm	Ø 160 x 31.5 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	UBIQUITI



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

SAP Code	300227850	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00